



NOTES:

- 1:100% short,open and miss wire test.
- 2:Insulation resistance:DC300V 10MΩ(Min)
Conduction resistance 5Ω(Max)

⑥	OUTER MOLDED	BLACK 45P PVC	0.03	KG
⑤	INTER MOLDED	LDPE	0.02	KG
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	2	PCS
③	CONNECTOR	HDB 15PIN/FEMALE WITH FRONT RIVET NUT,BLUE INSULATOR,NICKEL PLATED SHELL, GOLD PLATED PIN	2	PCS
②	CONNECTOR	HDB 15PIN/MALE BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	(1C*28#+D+AL+PVC)*3C+8C*28#+AL+D+B JACKET:BLACK PVC,OD:8.0±0.15 MARKING :AWM STYLE 2919 80°C 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	500	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

P2	1	Red coax conductor	P1	1	Red coax conductor	P3	1	Red coax conductor
	2	Green coax conductor		2	Green coax conductor		2	Green coax conductor
	3	Blue coax conductor		3	Blue coax conductor		3	Blue coax conductor
	4			4			4	
	5	Red coax drain		5	Red coax drain		5	Red coax drain
	6	Green coax drain		6	Green coax drain		6	Green coax drain
	7	Blue coax drain		7	Blue coax drain		7	Blue coax drain
	8			8			8	
	10			10			10	
	11			11			11	
	12			12			12	
	13			13			13	
	14			14			14	
	15	Drain		15	Drain		15	Drain
		shell			shell			shell

Ltref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference
Designed by ACHY	Checked by HELEN	Approved by - date OCT 16,2014	File name HDB15PIN M/F-2 L-0.2M
		Date OCT 16,2014	Scale FREE

24, 2980	24, 2980	1	1/1
----------	----------	---	-----