

3 Port Multi AV to HDMI Presentation Switch

Part No.: 38272



Description

- Supports direct conversion (no-scaling) of DisplayPort and VGA with Audio to HDMI
- Supports resolutions up to 4K Ultra HD 3840 x 2160p 60Hz
- Compatible with HDCP 2.2 protected content
- Switching by IR, Push Button and Auto-Sensing*
- 2 Year Warranty

* **Please Note:** Using the auto-sensing switching feature with the DisplayPort input requires the use of the supplied all pins connected 20 Pin DisplayPort cable between the source PC or Notebook and the switch.

Featuring DisplayPort, HDMI and VGA inputs which are automatically converted to HDMI for use with Displays and Projectors the Presentation Switch is an ideal addition to any meeting or conference room, lecture hall or auditorium. For added flexibility the Switch can be used with LINDY's range of HDMI Extenders to reach remote displays and projectors.

Package Contents:

DP/HDMI/VGA to HDMI Presentation Switch

IR Remote Control with 1 x CR2025 battery

Multi-Country Power Supply with UK, EU, US, AUS adapters +5V DC \geq 1 Amp

2m DisplayPort Cable (all pins wired)

2 x mounting brackets

User Manual

Technical details

- Input Ports: 1 x DisplayPort, 1 x HDMI & 1 x VGA + 3.5mm Audio
- Output Port: 1 x HDMI
- Supports up to 18 Gbps / 600 MHz bandwidth
- Supported Resolutions
- HDMI / DisplayPort up to UHD 4K 3840x2160p 60Hz 4:4:4 8bpc

- VGA up to 1920x1200p 60Hz RGB
- Digital Audio Pass-through, supports Dolby, DTS and PCM formats
- HDCP 2.2 compatible
- Switching via auto-sensing (DisplayPort requires all pins wired DisplayPort cable), IR & push button
- Operating temperature 0⁰C – 40⁰C
- Storage Temperature -20⁰C – 60⁰C
- Relative humidity: 0 – 60% RH (non condensing)
- Dimensions: 155 x 72 x 25 mm (WxDxH)
- Weight: 0.380kg