

Product datasheet

Specifications



APC SYMMETRA LX 9 BATTERY TOWER XR FRAME, 230V

SYBFXR9I

EAN Code: 0731304221715

Overview

Presentation Extended run power protection for servers, networks, and telecommunications

Main

Product or component type	Frame
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Installation guide User manual
Range of product	Symmetra Battery Systems

Batteries & Runtime

Battery location	Battery cabinet
Number of battery free slots	9
Number of battery filled slots	0
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
Battery voltage	120 V
Number of battery replacement quantity	9

Physical

Colour	Black
Height	602 mm
Width	483 mm
Depth	726 mm
Product weight	87.27 kg
Mounting mode	Not rack-mountable

Conformance

Standards	EN 50091-1 EN 50091-2 EN 60950 IEC 60950
Product certifications	BSMI VCCI VDE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...4572 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	91.4 cm
Package 1 Width	99.7 cm
Package 1 Length	59.9 cm
Package 1 Weight	119.09 kg

Logistical informations

Country of origin	PH
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	308 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	278 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	9 540 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	66
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



