

DATA SHEET



2-Port USB Wall Charger - AC to USB Adapter, 5V 4.8A Output

Simultaneously charge two mobile devices from a single outlet

OVERVIEW

The 2-Port USB Wall Charger - AC to USB Adapter is an ideal solution for charging a mobile device at home, in the office, or on the road. This adapter provides two ports with power outputs of 5 volts and 4.8 amps for device charging. The compact design of this adapter makes it easy to toss into a suitcase or backpack for charging on the go.

FEATURES

- 5V, 2.4A output per port
- 2 standard USB-A ports
- Compact size
- Foldable AC prongs

ITEM DESCRIPTION

20276 2-Port USB Wall Charger - AC to USB Adapter, 5V 4.8A Output

DATA SHEET

SPECIFICATIONS:

2-Port USB Wall Charger - AC to USB Adapter, 5V
4.8A Output

ELECTRICAL OUTPUT CHARACTERISTICS:

- Output voltage (no load): 4.9-5.25V
- Output voltage (full load): 4.75-5.25V
- Regulation: $\pm 5\%$
- Rated current: 4.8A

ELECTRICAL INPUT CHARACTERISTICS:

- Input voltage range: 90-264V AC
- Nominal input voltage: 100-240V AC
- Frequency range: 47-63Hz
- Input current with full load: $\leq 0.6A$
- Inrush current: 60A
- Efficiency: $\geq 84.05\%$ Level VI
- Standby power loss: $\leq 0.1W$

OPERATING ENVIRONMENT:

Temperature

- Operating: $-5^{\circ} - +40^{\circ}C$
- Storage: $-20^{\circ} - +70^{\circ}C$

Humidity

- Operating: 20% - 80% relative humidity (non-condensing)
- Storage: 10% - 90% relative humidity (non-condensing)

PHYSICAL CHARACTERISTICS:

- Dimensions (HxWxD): 2.50 x 1.15 x 2.00in

C2G[®]
A brand of **legrand**

3555 Kettering Blvd.
Moraine, OH 45439
Phone: 800.CABL.911
www.c2g.com

Follow Us

