

Delock Displayport 1.2 Splitter 1 x Displayport in > 2 x HDMI out 4K 30 Hz

Description

This splitter by Delock is suitable for the connection of two HDMI monitors to a computer with Displayport interface. Two monitors can be operated simultaneously at the outputs.

4K
30Hz



Note

The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.

Specification

- Connectors:
 - Input:
 - 1 x Displayport 20 pin male
 - 1 x USB Type Micro-B female (5 V power supply)
 - Output:
 - 2 x HDMI-A 19 pin female
- Chipset: STDP4320
- Displayport 1.2 specification
- Resolution up to 2560 x 1440 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Functions: Mirrored or Extended (Windows only)
- Transfer of audio and video signals
- Colour: black
- Cable length incl. connectors: ca. 25 cm
- Dimensions (LxWxH): ca. 61 x 49 x 11 mm

System requirements

- Windows 8.1/8.1-64/10/10-64, Mac OS 10.9
- One free Displayport female
- Displayport cable

Package content

- Displayport Splitter
- USB power cable, length: ca. 0.5 m
- User manual

Item no. 87720

EAN: 4043619877201

Country of origin: China

Package: Retail Box



Images



General	
Specification:	Displayport 1.2
Supported operating system:	Mac OS 10.9 Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Interface	
Output:	2 x HDMI-A 19 pin female
Input:	1 x Displayport 20 pin male 1 x USB Type Micro-B female (5 V power supply)
Technical characteristics	
Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Physical characteristics	
Housing colour:	black
Housing material:	Plastic
Cable length incl. connector:	25 cm
Length:	61 mm
Width:	49 mm
Height:	11 mm