

2 Port Professional USB KVM Switch Kit with Cables - TAA

Product ID: SV231USBGB



The SV231USBGB 2 Port Professional USB KVM Switch Kit with Cables offers simple control of 2 computers from a single monitor/display and USB peripheral set (keyboard, mouse).

The 2 Port KVM includes 2 USB KVM cables, for a complete out-of-the-box solution saving you time and money. An integrated 3 port USB hub allows you to share USB peripherals between computers as though they were connected directly. A compact form factor and rear-port connections minimizes disruption to your workspace.

This OS independent KVM supports resolutions up to 1920x1440, and provides a smooth operating experience in mixed (Windows/Mac/Linux) environments.

Certifications, Reports and Compatibility



Applications

- Dual system control for a single workstations increasing user productivity in the office
- Provide centralized control for multiple high-res Digital Signage server control
- Great for manufacturing line computer control, simplifying access to multiple systems

- Perfect for PC test/burn-in computer control saving the desk space required for two monitors, keyboards and mice

Features

- Control 2 computers from one USB keyboard/mouse/monitor
- Share 3 different USB peripherals using the integrated hub
- High 1920x1440 resolution capability
- Front panel push buttons for easy computer selection
- OS independent - No software or drivers required
- Supports keyboard and mouse plug and play
- Selectable auto scan time interval
- Supports DDC2B VGA monitors
- Universal Power Adapter with EU and UK prong types included

Hardware

| | |
|------------------------------|---------|
| Warranty | 3 Years |
| U Height | 1U |
| Audio | No |
| KVM Ports | 2 |
| PC Interface | USB |
| PC Video Type | VGA |
| Number of Monitors Supported | 1 |
| Rack-Mountable | No |
| Cables Included | Yes |
| Daisy-Chain | No |

Performance

| | |
|-------------------|----|
| On-Screen Display | No |
| DVI Support | No |

| | |
|----------------------------|-----------------------|
| IP Control | No |
| Hot-Key Selection | No |
| Maximum Cable Length | 16.4 ft [5 m] |
| Maximum Analog Resolutions | 1920x1440 |
| Auto Scan | 3, 8, 15 & 30 seconds |
| Maximum Number of Users | 1 |
| Port Selection Support | Push Button |
| MTBF | 111000 hours |

Connector(s)

| | |
|----------------------|---|
| Console Interface(s) | 3 - USB 2.0 Type-A (4 pin, 480Mbps) 1 - VGA (15 pin, High Density D-Sub) |
| Host Connectors | 2 - USB B (4 pin) 2 - VGA (15 pin, High Density D-Sub) |

Software

| | |
|------------------|---|
| OS Compatibility | OS independent; No software or drivers required |
|------------------|---|

Power

| | |
|-----------------------|---------------------|
| Power Source | AC Adapter Included |
| Input Voltage | 100 - 240 AC |
| Input Current | 0.4A |
| Output Voltage | 5 DC |
| Output Current | 2A |
| Center Tip Polarity | Positive |
| Plug Type | N |
| | N |
| Power Consumption (In | 10 |

Watts)

Physical Characteristics

| | |
|-------------------|-------------------|
| Color | Black |
| Material | Steel |
| Product Length | 4.9 in [12.4 cm] |
| Product Width | 2.8 in [7.0 cm] |
| Product Height | 1.6 in [4.0 cm] |
| Product Depth | 2.8 in [70 mm] |
| Weight of Product | 14.9 oz [421.0 g] |

Packaging Information

| | |
|---------------------------|------------------|
| Package Quantity | 1 |
| Package Length | 7.2 in [18.3 cm] |
| Package Width | 9.3 in [23.5 cm] |
| Package Height | 3.6 in [9.2 cm] |
| Shipping (Package) Weight | 2.6 lb [1.2 kg] |

What's in the Box

| | |
|---------------------|-------------------------------------|
| Included in Package | 1 - 2 Port KVM Switch |
| | 2 - 6ft(1.83m) KVM Cables |
| | 1 - Universal power adapter (EU/UK) |
| | 1 - User Manual |

Warranty Information

| | |
|----------|---------|
| Warranty | 3 Years |
|----------|---------|

**Product appearance and specifications are subject to change without notice.*