

4 Port DVI-I Dual Link, USB 2.0 & Audio KVM Switch Pro

No.: 39339



Description

- Control four DVI-I Dual Link computers with one keyboard, monitor and mouse
- True Transparent USB - supports all widely used mice & keyboards
- DDC support for "Plug & Play" monitors
- Independent audio switching meaning you can listen to music on computer while browsing the internet on the other
- 2 year warranty

The Lindy 4 Port DVI-I KVM switch allows you to control four DVI-Dual Link equipped computers using a single keyboard, monitor and mouse along with independent control over audio. An integrated USB 2.0 hub allows you to share USB devices such as pen drives, hard drives and printers, between the computers. Representing excellent value for money it can support both high resolution digital and analogue systems.

True Transparent USB Function

True Transparent USB switching is an advanced USB emulation technology. It allows the KVM to recognise specific Keyboard & Mouse models and emulate any of their associated special key and function information.

Unique Switching Options

A unique switching arrangement allows the built-in USB hub to be switched independently of the computers allowing you to print from one PC whilst playing games on another. Similarly, independent audio switching means you can listen to music from one computer while browsing the internet on the other.

DVI-I Support

Supports DVI-I dual link monitors and computers with video resolutions of up to 2560 x 1600. The switch can also be used with analogue VGA computers using compatible adapter cables.

Package Contents:

KVM Switch USB 2.0 PRO DVI-I Dual Link
Multi-country power supply
Lindy User manual

Technical details

Specifications

- AV Interface: DVI-I
- Console Interfaces: USB
- Interface Standard: DVI-I 2.0 (Single Link), USB 2.0
- Maximum Resolution:
 - DVI: 2560x1600@60Hz

- VGA: 2048x1536@30Hz
- HDCP Support: -
- Supported Audio: Analog Stereo
- Separate Audio Ports: 2 x 3.5mm (Female)
- Serial Interface: -
- Console Number: 1
- Max Number PC/Server: 4
- Cascadable: Yes
- Switching Method: Port Buttons, Hotkey Switching (Configurable Hotkeys)
- 19" Rack Mountable: -
- Special Features: Shared USB Ports

Connectors

- Console Interfaces: DVI-I (Female), USB Type A HID (Female), 2 x 3.5mm (Female)
- PC/Server Interfaces: 4 x DVI-I (Female), USB USB 2.0 Type B (Female), 2 x 3.5mm (Female)
- Other Interfaces: 2 x USB 2.0 Type A (Female) Shared Ports
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions WxDxH: 255x120x460mm (10.04x4.72x18.11in)
- Housing Material: Metal + Plastic Front Panel
- Net Weight: 1.25kg (2.76lb)
- Operating Temperature: 0°C - 50°C (32°F - 122°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 0~90% RH (non-condensing)
- Power Requirements: 9VDC 1.1A
- Colour: Silver

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 310x215x65mm (12,2x8,46x2,56in)
- Gross Weight: 1.64kg (3.62lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Content

- KVM Switch
- Multi-Country Power Supply (UK, Euro, US, AUS)
- LINDY Manual

Purchasing Information

- No.: 39339
- EAN: 4002888393393