

Delock PoweredUSB cable male 24 V > USB Type-B male + Hosiden Mini-DIN 3 pin male 3 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to connect a device with USB Type-B port and Hosiden Mini-DIN 3 pin power port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by Epson or Toshiba. The cable is used both for data transmission and for power supply of the connected device.



Specification


- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x USB Type-B male +
 - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
 - 26 AWG data line
 - 20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors (L): ca. 3 m

Item no. 85489

EAN: 4043619854899

Country of origin: China

Package: Poly bag



System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free USB Type-B port and a free Hosiden Mini-DIN 3 pin power female port

Package content

- PoweredUSB cable

Images



General	
Specification:	PoweredUSB
Interface	
Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x USB 2.0 Type-B mBle 1 x Hosiden Mini-DIN 3 pin male
Technical characteristics	
Data transfer rate:	USB 2.0 up to 480 Mb/s
Voltage:	24 V
Physical characteristics	
Cable diameter:	6.5 mm
Conductor gauge:	26 AWG data line 20 AWG power line
Shielding:	double
Length:	3 m
Colour:	black