

## DIGITUS® Line-Interactive USV, 1500VA/900W



✓ 4x safety outlets

✓ 2-6 ms transfer time (10 ms max.)

✓ Compact size

✓ Backup time: 10-12 mins

### Abstract

DIGITUS® Line-Interactive USV, 1500VA/900W, 12V/9Ah x 2 Batterie, 4x Schutzkontaktsteckdosen, LCD-Display

### Features

- Excellent micro process management guarantees a high reliability in case of electricity failure
- Auto restart while AC is recovering
- Cold start function
- Connection Type: 4x safety outlets, 2x RJ45, 1x RS232, 1x USB 2.0 type B
- Input voltage: 230 VAC
- Voltage range: 162-290 VAC
- Frequency range: 50 Hz (auto sensing)
- Output voltage: 230 VAC ± 10%
- AC voltage regulation (battery mode): 10%
- Capacity: 1500 VA/ 900 W
- Frequency range (battery mode): 50 Hz ± 1%
- Typical transfer time: 2-6 ms
- Battery: 12V/9Ah x 2
- Typical recharge time: 6-8 hours to recover 90% of capacity
- Alarm sounds: Battery mode (sounding every 10 sec.), low battery (sounding every second), overload (sounding every 0.5 seconds), fault (continuously sounding)
- Humidity: 0-95% RH @ 0 °C to +40 °C (non condensing)
- Noise level: Less than 40 dB
- Boost and buck AVR for voltage stabilization
- Dimensions (H x W x D): 198 x 158 x 380 mm
- Weight: 10.1 kg

## Product Overview

The DIGITUS® Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload-, discharge and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the DIGITUS® Line-Interactive UPS units.

## Product Number Information

### DIGITUS® Line-Interactive UPS, LED display

DN-170063 DIGITUS® Line-Interactive UPS, 600VA/360W, 12V/7Ah x 1 battery, 2x safety outlets, AVR, RJ-11, LED display

### DIGITUS® Line-Interactive UPS, LCD display

DN-170074 DIGITUS® Line-Interactive UPS, 1000VA/600W, 12V/7Ah x 2 battery, 4x safety outlets, AVR, USB, RS232, RJ11/RJ45, LCD display

DN-170075 DIGITUS® Line-Interactive UPS, 1500VA/900W, 12V/9Ah x2 battery, 4x safety outlets, AVR, USB, RS232, RJ-11/45, LCD display

DN-170076 DIGITUS® Line-Interactive UPS, 2000VA/1200W, 12V/9Ah x 2 battery, 4x safety outlets, AVR, USB, RS232, RJ-11/45, LCD display

## Product Images

