

DIGITUS USB Type-C™ Multiport Travel Dock, 6 Port

DA-70867

EAN 4016032450481



USB-C Multiport Travel Dock, 6 Port 4K, HDMI, 1x USB-C, 2x USB3.0, 2x card reader

With DIGITUS® USB Type-C™ Multiport Travel Dock, you always have the most important interfaces with you. The dock adds six ports to your laptop. It offers a video interface (HDMI). The highest possible supported resolution: Brilliant UHD (4K/30Hz). It also offers two USB 3.0 ports, one of which provides an extra charging function for mobile devices (BC 1.2). The dock also offers a USB-C™ port (Power Delivery 3.0 + data transfer). The whole thing is rounded off by two card readers (MicroSD, SDHC, SDXC / MMC). The compact size, low weight and stowable connecting cable make the Multiport Travel Dock the perfect companion for traveling and trips.

The most important interfaces are always there – expands your notebook by 6 additional ports via one single USB-C™ port

- 1 x HDMI (UHD resolution, 4K/30 Hz)
- 2 x USB 3.0 ports for high speed data transfer, one with a charging function (BC 1.2) for mobile devices (5V/1.5A)
- 1 x USB-C™ port - Power Delivery (PD) 3.0 (100W, 20V/5A max.) + data transfer (5 Gbit/s max.)
- 2 x Card readers (MicroSD / SDHC, SDXC, MMC)
- Supports Ultra HD (30Hz), 3840 x 2160p resolution (HDMI)
- Stowable USB-C™ connecting cable (10 cm) – the connecting cable can be stored in the casing
- USB-C™ version: USB 3.1 (Gen 1)
- Premium aluminum housing
- Ultra-compact size as well as low weight – perfect for travelling and out and about
- Color: silver
- Dimensions: L 11.0 x B 6.1 x H 1.5 cm
- Weight: 100 g

- Not all USB-C™ ports support all features of the USB Type-C™ standard. Make sure your notebook's USB-C™ port supports DisplayPort Alternate Mode (DP-Alt Mod) and USB Power Delivery (PD).
- The video output capability depends on the graphic card of your notebook and the connected monitor. Certain graphics cards have limited MST support, while some monitors also limit the available resolution.
- The used power supply must supply at least 60 watts to power a connected notebook as well as the docking station via the USB-C™ port
- The used power supply must supply at least 60 watts to power a connected notebook as well as the docking station via the USB-C™ port
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- Housing: Aluminum
- LAN connector (RJ45): no
- LAN connector (RJ45): no
- USB-C Power Delivery: 100W
- Card reader: yes
- Number of audio ports: 0
- Number of display ports: 1
- Number of network ports: 0
- Number of USB A ports: 2
- Number of USB-C ports: 2
- Number of video ports: 1
- USB-C Products: yes
- Video connection ports: HDMI

Package contents

- USB Type-C™ Multiport Travel Dock, 6-Port
- Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	7.50	38.50	22.00	26.00	22,022.00
Packaging Unit Inside	1	0.19	16.00	11.50	2.50	460.00
Packaging Unit Single	1	0.19	16.00	11.50	2.50	460.00
Net single without Packaging	1	0.10	11.00	6.10	1.50	0.00

More images:

