



High Speed HDMI Cable

ARC, 3D, 4K@30Hz, HDMI Male to Male, Shielded, 1.5 m (5 ft.), Black
Part No.: [355308](#)

EAN-13: 0766623355308 | UPC: 766623355308

A high-speed cable that delivers high-definition performance.

HDMI has become the standard digital connection, delivering the highest-quality audio and video signal over a single cable. The Manhattan High Speed HDMI Cable is designed and carefully constructed to meet the evolving needs of the high-definition marketplace. This shielded cable provides the highest resolution possible at 4K x 2K, an audio return channel and a bandwidth of 10.2 Gigabits per second at 340 MHz. Offering a high-quality connection between HDMI-enabled sources and displays, the Manhattan High Speed HDMI Cable provides ultra-high-definition video and multichannel, digital audio with increased performance characteristics and greater accuracy.

Features:

- 4K@30Hz Ultra-High-Definition (UHD) resolution supports video resolution up to four times that of 1080p; supports up to 1080p resolution in 3D and Deep Color
- Audio Return Channel (ARC) transmits TV audio through your sound system; no need for additional cable
- Tangle-resistant design allows for easier handling and management; resists cuts and nicks

- Ensures the integrity of the signal between HDMI devices
- Compliant with High Speed HDMI specifications
- Provides bandwidth up to 10.2 Gbps at 340 MHz
- Fully shielded to reduce EMI and other interference sources
- Compatible with any HDMI device, such as Blu-ray, game consoles, stereos, PCs and more
- Lifetime warranty

Specifications:

Standards and certifications

- ISO9001

General

- Bandwidth: 10.2 Gbps at 340 MHz
- Meets or exceeds existing HDMI standards
- Length: 1.5 m (5 ft.)

Connectors

- Two HDMI 19-pin male
- Gold-plated contacts
- Molded PVC boot
- Built-in strain relief

Cable

- 30 AWG cable
- Double shielded
- Current rating: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 5 Ohms
- Thermal plastic casing

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

Package Contents

- High Speed HDMI Cable

