



WD Green™ SSD (Solid State Drive)

For use in laptops and desktop computers, WD Green SSDs offer high performance and reliability to boost your daily computing activities. With comprehensive WD F.I.T. Lab™ certification, and available in 2.5"/7mm cased or M.2 2280 models, WD Green solid state drives are compatible with most PCs. The free WD SSD Dashboard lets you monitor your storage, and when combined with the 3-year limited warranty, upgrading your digital storage is worry-free.



INTERFACE	FORM FACTOR	CAPACITY
SATA III 6 Gb/s	2.5"/7mm cased M.2 2280	120GB – 480GB

Product Features

Improved performance for everyday computing

Enhance your system with a WD Green solid state drive and help improve the performance of your laptop or desktop computer for your daily computing needs. SLC (single-level cell) caching technology helps boost write performance in a WD Green SSD to browse the web, play your favorite casual games, or simply start up your system in a flash.

Solid state reliability

WD Green SSDs are built to be lightweight and shock-resistant to help protect against data loss if a drive is accidentally bumped or dropped. Combined with the comprehensive WD Functional Integrity Testing Lab (F.I.T. Lab™)

certification, every WD Green SSD is tested to ensure it meets the highest WD brand standards for digital storage. And with no moving parts in a WD Green SSD, you get reliable storage to withstand normal wear and tear for years to come.

Less power. More play.

WD Green solid state drives are among the lowest in power consumption in the industry. And with less power used, you can run your laptop PC for longer periods of time.

An easy upgrade for your PC

WD Green SSDs are available in a 2.5"/7mm cased model, and an M.2 2280 version to evolve with newer and smaller computers. With form factors to accommodate most laptop and desktop PCs, a WD Green SSD is ready for the job.

Free WD SSD Dashboard

The downloadable WD SSD Dashboard provides a suite of tools so you're always able to check on the health of your solid state drive. Available for free, this WD SSD Dashboard helps you track things like disk model, firmware version, S.M.A.R.T. attributes, or simply find out how much space you have left on your WD Green SSD.

3-year limited warranty

Every WD Green SSD comes with a 3-year limited warranty, so you can be confident of your storage when you upgrade or replace any of your drives.

Applications

WD Green SSDs are tested and recommended for use in desktop, all-in-one, and small form-factor PCs.

The WD Advantage

WD puts our products through extensive Functional Integrity Testing (F.I.T.) prior to any product launch. This testing ensures our products consistently meet the highest quality and reliability standards of the WD brand.

WD also has a detailed Knowledge Base with more than 1,000 helpful articles as well as software and utilities. Our customer support lines have long operational hours to ensure you get the help you need when you need it. Our toll-free customer support lines are here to help or you can access our WD Support site for additional details.



WD Green™ SSD

Specifications*	480GB	240GB	120GB
Model Numbers¹			
WD Green SSD 2.5"/7mm cased	WDS480G2G0A	WDS240G2G0A	WDS120G2G0A
WD Green SSD M.2 2280	WDS480G2G0B	WDS240G2G0B	WDS120G2G0B
Interface^{2,3}			
WD Green SSD 2.5"/7mm cased	SATA III 6 Gb/s	SATA III 6 Gb/s	SATA III 6 Gb/s
WD Green SSD M.2 2280	SATA III 6 Gb/s	SATA III 6 Gb/s	SATA III 6 Gb/s
Performance⁴ [4KB QD32]			
Sequential Read up to (MB/s)	545	545	545
Power⁵			
Average Active Power (mW)	80	80	80
Max Read Operating (mW)	2800	2800	2200
Max Write Operating (mW)	2800	2800	2200
Slumber (mW)	30	30	30
DEVSLP (mW)	10	10	10
Reliability			
MTTF ⁶	Up to 1.00M hours	Up to 1.00M hours	Up to 1.00M hours
Environmental			
Operating Temperatures	0°C to 70°C	0°C to 70°C	0°C to 70°C
Non-operating Temperatures	-55°C to 85°C	-55°C to 85°C	-55°C to 85°C
Operating Vibrations	5.0 gRMS, 10–2000 Hz	5.0 gRMS, 10–2000 Hz	5.0 gRMS, 10–2000 Hz
Non-operating Vibrations	4.9 gRMS, 7–800 Hz	4.9 gRMS, 7–800 Hz	4.9 gRMS, 7–800 Hz
Shock	1,500 G @ 0.5 msec half sine	1,500 G @ 0.5 msec half sine	1,500 G @ 0.5 msec half sine
Certifications	FCC, UL, TUV, KC, BSMI, VCCI	FCC, UL, TUV, KC, BSMI, VCCI	FCC, UL, TUV, KC, BSMI, VCCI
Limited Warranty ⁷	3 years	3 years	3 years
Physical Dimensions			
Size: 2.5"/7mm cased	7.00mm x 69.85mm x 100.50mm	7.00mm x 69.85mm x 100.50mm	7.00mm x 69.85mm x 100.50mm
Size: M.2 2280	1.5mm x 22.0mm x 80mm	1.5mm x 22.0mm x 80mm	1.5mm x 22.0mm x 80mm
Weight: 2.5"/7mm cased	32.7g, ± 0.5g	32.2g, ± 0.5g	32.1g, ± 0.5g
Weight: M.2 2280	6.52g, ± 0.5g	6.51g, ± 0.5g	6.46g, ± 0.5g

* Specifications subject to change without notice.

¹ Not all products may be available in all regions of the world.

² Backward compatible to SATA II and I.

³ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 6 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

⁴ Performance is based on the CrystalDiskMark benchmark using a 1000MB LBA range on ASUS Z170A ATX desktop with Intel Z170 chipset, Intel i7-6700K 4.0GHz, 8M, Skylake, 8GB 2133MHz DDR4, Windows 10 Pro 64-bit using Intel iRST version 15.2.0.1020, secondary drive, C-state off. Performance may vary based on host device. 1 MB = 1,000,000 bytes. IOPS = input/output operations per second.

⁵ Measured using the MobileMark™ 2014 benchmark with DIPM (Device Initiated Power Management) enabled.

⁶ MTTF = Mean Time To Failure based on internal testing using Telcordia stress part testing.

⁷ See support.wdc.com for regional specific warranty details.

Western Digital
3355 Michelson Drive, Suite 100
Irvine, California 92612
U.S.A.

For service and literature:

support.wdc.com
www.wdc.com

800.ASK.4WDC (800.275.4932) North America
800.832.4778 Spanish
+86.21.2603.7560 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/
Africa



Western Digital, WD, the WD logo, F.I.T. Lab and WD Green are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All other marks are the property of their respective owners. Pictures shown may vary from actual products. Product specifications subject to change without notice.

© 2018 Western Digital Corporation or its affiliates. All rights reserved.

2879-800082-A02 January 2018