

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2197

Model Number: EGVHVRN102-102I82PS6-IP44

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU, Basic Standard, 16A, 230V, 3.6kW, Horizontal, (8) IEC C13, (2) IEC C19, 3m power cord with 2P+E (IP44), Black Powder Coat.

Plug Form:



2P+E (IP44)

Receptacle:



IEC C13
(Quantity: 8)



IEC C19
(Quantity: 2)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Vertiv.com | Vertiv Headquarters, 1050 Dearborn Drive, Columbus, OH, 43085, USA

© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

| | |
|---|---|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 16A |
| VA per Input (Load Capacity) | 3.6kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | No |
| Power Cable Wire Gauge | 2.5mm² H07RN-F |
| Power Cable Length | 3m |
| Plug Type | IEC60309 2P + E, 16A, 250V, Splashproof IP44 |
| Combined Total Receptacle/Socket Quantity | 10 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 8 |
| - Style | Banks of 2 |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank |
| - Voltage per Receptacle/Socket | 230V |
| Receptacle/Socket Type #2 | IEC C19 |
| - Quantity on Face | 2 |
| - Style | Individual |
| - Maximum Output per Receptacle/Socket | 16A |
| - Voltage per Receptacle/Socket | 230V |
| Continuous Operating Temperature Range | 10-45C / 50-113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 19in / 483mm Horizontal Rackmount |
| Flush Mount | Yes |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55024 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | RCM Mark (EMC Only) |
| Certification/Agency Approvals | C _P Mark |
| Chassis Dimensions (HxWxD) | 44mm x 435mm x 100mm |
| Shipped Weight | 4lbs (1.81kg) |