



WT6x Series Technical Accessory Guide



NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

** Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.*

Cradles/Charging

Part Number	Picture	Description	Notes	Required Items
CRD-NGWT-1S1BU-01		Single Slot Cradle	<ul style="list-style-type: none"> Provides USB support Supports terminal and spare battery charging LED notification of spare battery charging status. 	<ul style="list-style-type: none"> Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) AC Line Cord (23844-00-00R). Also requires Micro USB Cable (25-124330-01R) for host communication.
CRD1SLOT-WM-WT6000		Single Slot Cradle Kit	<ul style="list-style-type: none"> Provides USB support Supports terminal and spare battery charging LED notification of spare battery charging status. Kit includes Single Slot Cradle (CRD-NGWT-1S1BU-01), Power Supply (PWR-BGA12V50W0WW), DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R). NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	<ul style="list-style-type: none"> Requires Micro USB Cable (25-124330-01R) for host communication.
CRD1SLT-WM-WT6-INT		Single Slot Cradle Kit	<ul style="list-style-type: none"> Provides USB support Supports terminal and spare battery charging LED notification of spare battery charging status. Kit includes Single Slot Cradle (CRD-NGWT-1S1BU-01), Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01). NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	<ul style="list-style-type: none"> AC Line Cord (23844-00-00R). Requires Micro USB Cable (25-124330-01R) for host communication.

CRD-NWTRS-2SUCH-01		Single Slot Cradle for WT6000 and RS6000	<ul style="list-style-type: none"> •Provides USB support to WT6000 and RS6000 •Supports WT6000 and RS6000 •Does not support spare battery charging •LED notification of spare battery charging status. 	<ul style="list-style-type: none"> •Power Supply (PWR-BGA12V50W0WWW and CBL-DC-388A1-01) •AC Line Cord (23844-00-00R). •Also requires Micro USB Cable (25-124330-01R) for host communication.
CRD-NGWT-5S5BC-01		5-Slot Charge Only Cradle	<ul style="list-style-type: none"> •Charges 5 WT6000 units and 5 spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WWW) •AC Line Cord (23844-00-00R)
CRD5SLOT-WM-WT6000		5-Slot Charge Only Cradle Kit	<ul style="list-style-type: none"> •Charges 5 WT6000 units and 5 spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). •Kit includes 5-Slot Charge Only Cradle (CRD-NGWT-5S5BC-01), DC Line Cord (CBL-DC-382A1-01), Power Supply (PWR-BGA12V108W0WWW) and AC Line Cord (23844-00-00R). •NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
CRD5SLT-WM-WT6-INT		5-Slot Charge Only Cradle Kit	<ul style="list-style-type: none"> •Charges 5 WT6000 units and 5 spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). •Kit includes 5-Slot Charge Only Cradle (CRD-NGWT-5S5BC-01), DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WWW). •NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	<ul style="list-style-type: none"> •AC Line Cord (23844-00-00R)
CRD-NGWT-10SCH-01		10-Slot Charge Only Cradle	<ul style="list-style-type: none"> •Charges 10 WT6000 units •Does not charge spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WWW) •AC Line Cord (23844-00-00R)
CRD-NWTRS-10SCH-01		10-Slot Charge Only Cradle for WT6x and RS6x	<ul style="list-style-type: none"> •Charges 5 WT6x units and 5 RS6x units •Does not charge spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WWW) •AC Line Cord (23844-00-00R)

<p>CRD-10NW-GRD-01</p>		<p>10-Slot Charge Only Cradle for WT6x and RS6x Kit</p>	<ul style="list-style-type: none"> •Charges 5 WT6x units and 5 RS6x units •Does not charge spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). •Kit includes 10-Slot Charge Only Cradle for WT6x and RS6x(CRD-NWTRS-10SCH-01), Power Supply (PWR-BGA12V108W0WW), DC Line Cord (CBL-DC-382A1-01) and AC Line Cord (23844-00-00R). •NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
<p>CRD-8NW-GRD-01</p>		<p>8-Slot Charge Only Cradle for WT6x, RS6x and Spare Batteries Kit</p>	<ul style="list-style-type: none"> •Charges 4 WT6x units, 4 RS6x units and 4 Spare WT6x/RS6x Spare Batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). •Kit includes 8-Slot Charge Only Cradle for WT6x, RS6x and Spare Batteries (CRD-NWTRS-8SC4B-01), Power Supply (PWR-BGA12V108W0WW), DC Line Cord (CBL-DC-382A1-01) and AC Line Cord (23844-00-00R). •NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
<p>SAC-HS3100-B8W8-01</p>		<p>8-Slot Charge Only Cradle for WT6000 and HS3100 batteries</p>	<ul style="list-style-type: none"> •Charges 8 WT6000 units and 8 HS3100 Batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) •AC Line Cord (23844-00-00R)
<p>CRD-NGWT-5S5BE-01</p>		<p>5-Slot Ethernet + Charge Cradle</p>	<ul style="list-style-type: none"> •Allows Ethernet speeds up to 1 Gb •Charges 5 terminals and 5 spare batteries •Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) •AC Line Cord (23844-00-00R)
<p>SAC-NWTRS-4SCH-01</p>		<p>4-Slot Battery Charger</p>	<ul style="list-style-type: none"> •Charges up to 4 Spare Batteries •Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> •Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) •AC Line Cord (23844-00-00R).

SACWT60-4-WM		4-Slot Battery Charger Kit with AC Line Cord	<ul style="list-style-type: none"> Charges up to 4 Spare Batteries Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). Kit includes 4-Slot Battery Charger (SAC-NWTRS-4SCH-01), Power Supply (PWR-BGA12V50W0WW), DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R). NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
SACWT60-4-WM-INT		4-Slot Battery Charger Kit	<ul style="list-style-type: none"> Charges up to 4 Spare Batteries Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). Kit includes 4-Slot Battery Charger (SAC-NWTRS-4SCH-01), Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01). NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	AC Line Cord (23844-00-00R)
SAC-NWTRS-20SCH-01		20-Slot Battery Charger	<ul style="list-style-type: none"> Charges up to 20 Spare Batteries Can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01) 	<ul style="list-style-type: none"> DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) AC Line Cord (23844-00-00R)
SAC-20SLOT-GRD-01		20-Slot Battery Charger Kit	<ul style="list-style-type: none"> Charges up to 20 Spare Batteries Can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). Kit includes 20-Slot Battery Charger (SAC-NWTRS-20SCH-01), DC Line Cord (CBL-DC-382A1-01), Power Supply (PWR-BGA12V108W0WW) and AC Line Cord (23844-00-00R). NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
BRKT-SCRD-SMRK-01		Multi-Slot Wall/Rack Mount Bracket	<ul style="list-style-type: none"> Allows for rack and wall mounting of one 5-Slot, 10-Slot, or 20-Slot Charger. Also can be used to mount up to four 4-Slot Battery Chargers or Single-Slot Cradles Bracket can be mounted on standard 19" network rack or on a wall. Cable routing slots & removable power supply holder tray. Adjustable tabs & screw mounts for easy hanging/installation. Adjustable orientations - horizontal, vertical, angled. See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	

Communication Cables

Part Number	Picture	Description	Notes	Required Items
25-124330-01R		USB Cradle to PC/Host cable	►Micro USB connection on cradle end	
CBL-NGWT-USBCHG-01		Snap-on USB Communication/Charging Cable	►Attaches to one of the accessory ports on WT6000	Power Supply (PWR-BUA5V16W0WW), DC Line Cord (CBL-DC-383A-01) and AC Line Cord (50-16000-182R) for charging
CBL-NGWT-USBH1-01		WT6000 to USB-A Adapter Cable	►Connects to WT6000 to accessories with USB-A connector (i.e. USB stick, keyboard, mice, etc.). ►Typically used with the prototype version of Darwin HUD. ►NOTE: This is a custom product. Please work with your Zebra representative to obtain Product Management approval if you would like to order this item.	
3rd party *		USB micro-A to USB A Female adapter	►Allows the TC8000 to act as a USB host to connect to devices like USB flash drives/memory sticks, mice, etc. ►Connects to 2-Slot USB/Charge ShareCradle	

(see <http://www.cyberguys.com/product-details/?productid=33062>)

Soft Goods - Cases/Holsters

Part Number	Picture	Description	Notes	Required Items
SG-NGWT-WRMTS-02		Wrist Mount (Standard Strap)	►Uses BOA dia-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-02) and Small/Medium size Wrist Strap (SG-NGWT-WSTPST-01). ►White Dial and accent color on strap identify size as Standard (small/medium). ►Strap length can be adjusted between 128 to 191 mm (approx 5.0 to 7.5") ►It is typical for each user to have their own wrist mount (for hygiene). ►Improved design vs. SG-NGWT-WRMTS-01 uses updated Comfort Pad (SG-NGWT-CMPD-02) which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat.	

SG-NGWT-WRMTL-02		Wrist Mount (Extended Strap)	<ul style="list-style-type: none"> ▶Uses BOA dial-to-fit design which is strong, durable, and easy to use. ▶Velcro free design uses non-absorbent materials that can be wiped down. ▶Includes Carrier, Comfort Pad (SG-NGWT-CMPD-02) and Medium/Large size Wrist Strap (SG-NGWT-WSTPLN-01). ▶Black Dial and accent color on strap identify size as Extended (medium/large). ▶Strap length can be adjusted between 164 to 265 mm (approx 6.5 to 10.5") ▶It is typical for each user to have their own wrist mount (for hygiene). ▶Improved design vs. SG-NGWT-WRMTL-01 uses updated Comfort Pad (SG-NGWT-CMPD-02) which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat 	
SG-NGWT-WRMTXL-01		Wrist Mount (Extra Large Length Strap)	<ul style="list-style-type: none"> ▶Uses BOA dial-to-fit design which is strong, durable, and easy to use. ▶Velcro free design uses non-absorbent materials that can be wiped down. ▶Includes Carrier, Comfort Pad (SG-NGWT-CMPD-01) and Extra-Large size Wrist Strap (SG-NGWT-WSTPXL-01). ▶Blue Dial and accent color on strap identify size as Extra-Large. ▶Strap length is 375 mm (approx 14.75") ▶This size strap is typically used in freezer environments where users may be wearing heavy jackets. ▶It is typical for each user to have their own wrist mount (for hygiene). 	
SG-NGWT-CMPD-02		Replacement Comfort Pad for wrist mount	<ul style="list-style-type: none"> ▶Soft Rubber ▶Easily removable ▶Hygienic ▶Improved design vs. SG-NGWT-CMPD-01 which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat. 	
SG-NGWT-CMPD-01		Replacement Comfort Pad for wrist mount	<ul style="list-style-type: none"> ▶Soft Rubber ▶Easily removable ▶Hygienic 	

<p>SG-NGWT-WSTPST-01</p>		<p>Replacement Wrist Strap (standard size)</p>	<ul style="list-style-type: none"> ▶White Dial and accent color on strap identify size as Standard (small/medium) ▶Strap length can be adjusted between 128 to 191 mm (approx 5.0 to 7.5") 	
<p>SG-NGWT-WSTPLN-01</p>		<p>Replacement Wrist Strap (extended size)</p>	<ul style="list-style-type: none"> ▶Black Dial and accent color on strap identify size as Extended (medium/large) ▶Strap length can be adjusted between 164 to 265 mm (approx 6.5 to 10.5") 	
<p>SG-NGWT-WSTPXL-01</p>		<p>Replacement Wrist Strap (extra-large size)</p>	<ul style="list-style-type: none"> ▶Blue Dial and accent color on strap identify size as extra-large. ▶Strap length can be adjusted between 218 to 375 mm (approx 8.5 to 14.75") 	

SG-WT4027050-01R		Arm Sleeve (pack of 5)	<ul style="list-style-type: none"> ▶Worn under WT6000 wrist mount if worker is in short-sleeved shirt and wants: <ul style="list-style-type: none"> - Extra sweat wicking/ personal layer - Extra comfort - Extra slip-resistance ▶Material will not snag ▶One size fits all ▶Washable in mild detergent. Should be air dried. ▶Pack of 5 Arm Sleeves 	
(3rd party) *		Arm Sleeve	<ul style="list-style-type: none"> ▶Can be worn under WT6000 Wrist Mount in environments where excessive user sweat may cause the strap to slip ▶Also can be worn by users that may have skin irritations from the wrist mount 	
SG-NGWT-HPMNT-01		Hip-mount Clip	<ul style="list-style-type: none"> ▶Allows WT6000 to be worn on hip ▶Will attach to clothing, user's belt, or optional Belt for Hip-mount Clip (11-08062-02R) 	
SG-NGWT-HPMNT-02		Hip-mount Clip	<ul style="list-style-type: none"> ▶Allows WT6000 to be worn on hip ▶Will attach to clothing, user's belt, or optional Belt for Hip-mount Clip (11-08062-02R). ▶This Clip holds the WT6000 in the reverse orientation of SG-NGWT-HPMNT-01. ▶NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
(3rd party) *		Additional holsters		
11-08062-02R		Belt for Hip-mount Clip	<ul style="list-style-type: none"> ▶Belt is 2 inches wide ▶Extends to 48 inches ▶Has improved buckle and softer belt material 	

V6198DW (3rd party) * http://www.ultimacase.com		Belt Extender	►Used to extend the Hip-mount belt (11-08062-02R) an additional 10 inches	
---	---	---------------	---	--

Ring Scanner (RS5000) - 2D Imager

Part Number	Picture	Description	Notes	Required Items
RS5000-LCFSWR		RS5000 Ring Scanner with short cable (for wrist mount)	►Uses SE4710 scan engine. ►IP54 sealed ►Extended temperature spec down to -30C for freezer environments.	
RS5000-LCFLWR		RS5000 Ring Scanner with long cable (for hip mount)	►Uses SE4710 scan engine. ►IP54 sealed ►Extended temperature spec down to -30C for freezer environments.	
SG-NGRS-SFSVS-01R		RS5000 Spare Ring Scanner Strap (Short)	►Short finger strap - 6" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►This is the same strap that is included on each RS5000.	
SG-RS419-FGSTP-02R		RS4000/RS5000/ RS409/RS419 Spare Ring Scanner Strap (Long)	►Improvements include a new connection between the velcro and fabric used as part of the accessory. ►Long finger strap - 7.8" long ►It is typical for each user to have their own ring scanner strap (for hygiene).	
SG-NGRS-TRGASR-01R		RS5000 Replacement Trigger Assembly	►Uses same design as RS419 Trigger (SG-RS419-TRGAS-01R), but doesn't include laser warning label on trigger button.	

Ring Scanner (RS6000) - 2D Cordless Bluetooth Imager (see RS6000 Accessories document)

Ring Scanner (RS4000) - 1D Laser

Part Number	Picture	Description	Notes	Required Items
RS4000-HPCSWR		RS4000 Ring Scanner with short cable (for wrist mount)	►Uses SE965 scan engine with Adaptive Scanner for longer read ranges (near contact to 200 inches). ►Extended temperature spec down to -30C for freezer environments.	
RS4000-HPCLWR		RS4000 Ring Scanner with long cable (for hip mount)	►Uses SE965 scan engine with Adaptive Scanner for longer read ranges (near contact to 200 inches). ►Extended temperature spec down to -30C for freezer environments.	

SG-RS419-FGSTP-02R		RS4000/RS5000/ RS409/RS419 Spare Ring Scanner Strap (Long)	<ul style="list-style-type: none"> Improvements include a new connection between the velcro and fabric used as part of the accessory. Long finger strap - 7.8" long It is typical for each user to have their own ring scanner strap (for hygiene). This is the same strap that is included on each RS419. 	
21-93022-03R		RS4000/RS409/RS419 Spare Ring Scanner Strap (Short)	<ul style="list-style-type: none"> Improvements include a new connection between the velcro and fabric used as part of the accessory. assembly over previous version. Short finger strap - 6" long It is typical for each user to have their own ring scanner strap (for hygiene). This is the same strap that is included on each RS409. 	
SG-RS419-TRGAS-01R		RS4000/RS419 Replacement Trigger Assembly	Internal P/N - 21-156086-01	

Headset/Audio Accessories

Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document		HS2100 Rugged Wired Headset	<ul style="list-style-type: none"> Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzero temperatures Feather-light for extraordinary comfort Noise cancellation for a superior voice experience in the noisiest environments Detachable swivel boom minimizes costs. Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. User-replaceable pads and windscreens maximize comfort and hygiene 	<u>Requires one of the following cable options:</u> (1) HS2100 to WT6000 Cable (CBL-HS2100-12S1-01) OR (2) Quick Disconnect Headset cable (CBL-HS2100-QDC1-02) AND WT6000 to Quick Disconnect Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02) See HS2100/HS3100 Accessories Document for additional headset accessories
VR12 (3rd party) * http://www.blueparrott.com		BlueParrott VR12 Wired Noise Cancelling Headset	<ul style="list-style-type: none"> Audio accuracy for voice picking and other speech recognition applications. High quality durability stands up to all-day, every-day use. Lightweight design is easy and comfortable to wear all day. Compatible with most major wearable computers and devices used in voice-picking environments. G type (GN Netcom) Quick Disconnect. Convertible design gives choice of over-the-head and behind-the-neck wearing styles 	Quick Disconnect Headset to WT6000 Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02)

<p>See HS2100-HS3100 Accessories Document</p>		<p>HS3100 Rugged Bluetooth Headset</p>	<ul style="list-style-type: none"> ▶HD Voice, also known as Wide Band Audio, brings incredible audio clarity ▶Built to handle the everyday inevitable drops ▶Dustproof, sprayproof and waterproof ▶Ready for the freezer and outdoor subzero temperatures ▶Feather-light for extraordinary comfort ▶Noise cancellation for a superior voice experience in the noisiest environments ▶Swap batteries on the fly — without losing the Bluetooth connection ▶Split-second tap-to-pair simplicity using NFC. ▶Detachable swivel boom minimizes costs. ▶Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ▶User-replaceable pads and windscreens maximize comfort and hygiene ▶15 hours of battery power 	<p>See HS2100/HS3100 Accessories Document for headset accessories</p>
<p>various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com</p>		<p>BlueParrott Bluetooth Headsets</p>	<ul style="list-style-type: none"> ▶Various Bluetooth models available with options that include: <ul style="list-style-type: none"> - Blocking out 96% of background noise - Over 24 hours of talk time - NFC Tap to Pair capable - Bluetooth wireless range capable up to 300 ft. - Convertible wearing options: over the head, behind the neck. <p>See BlueParrot site for model specific options.</p>	
<p>APTT1 (3rd party) * https://www.aina-wireless.com</p>		<p>Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶Features several buttons which the application developers can assign to different functions. ▶Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ▶Device is ruggedized, MIL-STD 810G and IP67. ▶Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ▶Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶Can be easily paired to mobile computer using NFC tap-to-pair. 	

<p>H3-B-1 (3rd party) *</p> <p>https://www.dellking.com</p>		<p>Wandfu H3 Push-To-Talk (PTT) Bluetooth Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. 	
<p>BTR-155 (3rd party) *</p> <p>K551011 (Zebra orderable SKU) ▶Discontinued 3/2019, now order from Savox</p> <p>https://www.savoxaccessories.com</p>		<p>Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶Rugged wireless speaker microphone, IP55. ▶Allows cable-free movement ▶Familiar speaker microphone functions; PTT and volume buttons ▶Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶LED status indication ▶High speaker volume ▶Includes: <ul style="list-style-type: none"> - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap 	
<p>BTH-101 (3rd party) *</p> <p>https://www.savoxaccessories.com</p>		<p>Savox Push-To-Talk (PTT) Bluetooth Headset</p>	<ul style="list-style-type: none"> ▶Bluetooth headset designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Also operates as standard Bluetooth headset for taking phone calls. ▶Device is lightweight and ruggedized, IP55. 	

CBL-HS2100-12S1-01		HS2100 Headset to WT6000 cable	<ul style="list-style-type: none"> Connects HS2100 directly to WT6000 43" long straight cable Includes one clip for attaching to clothing. Additional clips can be purchased separately. 	
CBL-NGWT-AUQDST-02		Headset Adapter Cable (short cable)	<ul style="list-style-type: none"> Connects wired headsets with Quick Disconnect connector (i.e. HS2100/ RCH50/ RCH51, BlueParrot, Vowware, and Eartec headsets) to WT6000 Cable is used when WT6000 is worn on the wrist. Provides additional strength on Quick Disconnect connector vs. CBL-NGWT-AUQDST-01. 	
CBL-NGWT-AUQDLG-02		Headset Adapter Cable (long cable)	<ul style="list-style-type: none"> Connects wired headsets with Quick Disconnect connector (i.e. HS2100 / RCH50 RCH51, BlueParrot, Vowware, and Eartec headsets) to WT6000 Cable is used when WT6000 is worn on the hip. Provides additional strength on Quick Disconnect connector vs. CBL-NGWT-AUQDLG-01. 	
25-129938-02R		Headset Training Y cable	<ul style="list-style-type: none"> Connects two Quick Disconnect wired headsets to the WT6000 Extra cable to plug in a second headset or external speakers for training or performing a demo 	

Heads Up Display (HUD) Accessories

Part Number	Picture	Description	Notes	Required Items
HD4000-P		Darwin Heads Up Display Kit (no camera)	<ul style="list-style-type: none"> Darwin HUD integrates a see-through display, microphone, and IMU sensor into the industry's smallest form factor. A fully adjustable frame mount accommodates left or right eye use, a wide range of inter-pupillary distance positioning and the ability to flip the display up out of view. Built-in features include the ability to mirror the onscreen content from the WT6000 or use the HUD as a second screen through android presentation mode. Kit includes: <ul style="list-style-type: none"> Darwin HUD device with safety eyewear mount Rugged Optic Protector Pair of Safety Glasses (ESS Crosshair model) Microfiber drawstring bag This is the prototype release of the HUD which uses a standard USB-A cable connection. NOTE: This is a custom product. Please work with your Zebra representative to obtain Product Management approval if you would like to order this item. 	WT6000 to USB-A Adapter Cable (CBL-NGWT-USBH1-01)

HD4000-PC		Darwin Heads Up Display Kit (with camera)	<ul style="list-style-type: none"> ▶Darwin HUD integrates a seethrough display, microphone, and IMU sensor into the industry's smallest form factor. ▶A fully adjustable frame mount accommodates left or right eye use, a wide range of inter-pupillary distance positioning and the ability to flip the display up out of view. ▶Built-in features include the ability to mirror the onscreen content from the WT6000 or use the HUD as a second screen through android presentation mode. ▶Kit includes: <ul style="list-style-type: none"> - Darwin HUD device with integrated 5 MP color camera and safety eyewear mount - Rugged Optic Protector - Pair of Safety Glasses (ESS Crosshair model) - Microfiber drawstring bag ▶This is the prototype release of the HUD which uses a standard USB-A cable connection. ▶NOTE: This is a custom product. Please work with your Zebra representative to obtain Product Management approval if you would like to order this item. 	WT6000 to USB-A Adapter Cable (CBL-NGWT-USBH1-01)
CBL-NGWT-USBH1-01		WT6000 to USB-A Adapter Cable	<ul style="list-style-type: none"> ▶Connects to WT6000 to accessories with USB-A cable. ▶Typically used with the prototype version of Darwin HUD. ▶NOTE: This is a custom product. Please work with your Zebra representative to obtain Product Management approval if you would like to order this item. 	

Misc

Part Number	Picture	Description	Notes	Required Items
CBL-NGWT-HDVBAP-01		Vibrating Cable	<ul style="list-style-type: none"> ▶Connects to WT6000 and provides additional haptic feedback to user. ▶Cable is normally attached to user's wrist ▶Can be used in noisy environments or for hearing impaired users. 	
MISC-WT6X-SCRN-01		Screen Protector (pack of 5)		

Power Cords/Power Supplies

Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------

CBL-DC-388A1-01		DC Power Cord	<ul style="list-style-type: none"> Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot Cradle and 4-Slot Battery Charger. Cable length is 1.8 meters 	
PWR-BGA12V50W0WW		Power Supply	<ul style="list-style-type: none"> Used to power Single Slot Cradle and 4-Slot Battery Charger. 100-240 VAC, 12V, 4.16A, 50W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-148R 	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R)
KIT-PWR-12V50W		Power Supply Kit	<ul style="list-style-type: none"> Includes Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01) 	AC Line Cord (23844-00-00R)
CBL-DC-383A1-01		DC Line Cord	<ul style="list-style-type: none"> Used to power Snap-On USB/Charge Cable with Power Supply PWR-BUA5V16W0WW Cable length is 6 ft. 	
PWR-BUA5V16W0WW		Power Supply	<ul style="list-style-type: none"> Used with Snap-On USB/Charge Cable 100-240VAC, 5.4V, 3A, 16W Meets US DOE Level VI efficiency standard Replaces PWRS-14000-249R 	DC Line Cord (CBL-DC-383A1-01) and AC Line Cord (50-16000-182R)
CBL-DC-381A1-01		DC Power Cord	<ul style="list-style-type: none"> Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles. CBL-DC-382A1-01 is still typically used though. 	
CBL-DC-382A1-01		DC Power Cord	<ul style="list-style-type: none"> Used with Power Supply PWR-BGA12V108W0WW to power 5-Slot, 10-Slot, 20-Slot Cradles 	
PWR-BGA12V108W0WW		Power Supply	<ul style="list-style-type: none"> Used to power 5-Slot, 10-Slot, 20-Slot Cradles 100-240 VAC, 12V, 9A, 108W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-241R 	CBL-DC-382A1-01 and 23844-00-00R
23844-00-00R		AC Line Cord	Used to power all cradles	

50-16000-182R		AC Line Cord	Used with PWR-BUA5V16W0WW to power Snap-on charging cables	
---------------	---	--------------	--	--

Batteries				
------------------	--	--	--	--

Part Number	Picture	Description	Notes	Required Items
BTRY-NWTRS-33MA-02		Spare Standard Capacity Battery with PowerPrecision+ (3350 mAh) 	<ul style="list-style-type: none"> ▶Has improved battery latching mechanism vs. BTRY-NWTRS-33MA-01 ▶Designed, manufactured & tested to meet rigorous controls & standards ▶Premium-grade cells with higher capacity & longer life cycle ▶Designed to help prevent overcharging & electrical shock ▶Strong & robust housing for optimal performance & durability ▶Information available: <ul style="list-style-type: none"> - Available charge status - Total charge accumulated on the battery - Basic state of health ▶Compatible with WT6000 and RS6000 	
BTRY-NGWT-50MA-01		Spare Extended Capacity Battery with PowerPrecision+ (5000 mAh) 	<ul style="list-style-type: none"> ▶Provides 50% more battery capacity than Standard Capacity Battery. ▶Provides operating temperature spec down to -30°C, for cold chain and freezer use cases. ▶Designed, manufactured & tested to meet rigorous controls & standards ▶Premium-grade cells with higher capacity & longer life cycle ▶Designed to help prevent overcharging & electrical shock ▶Strong & robust housing for optimal performance & durability ▶Information available: <ul style="list-style-type: none"> - Available charge status - Total charge accumulated on the battery - Basic state of health ▶Only compatible with WT6000. Not compatible with RS6000 Ring Scanner. ▶When charging while in WT6000, device must be inserted into cradle via cradle contacts on left side of device. 	