

## Delock Adapter SMA jack to RP-SMA jack 90° 3 GHz

### Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



### Specification

- Connectors:
  - 1 x SMA jack >
  - 1 x RP-SMA jack 90°
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Frequency range: 3 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxW): ca. 15.15 x 15.15 mm

### System requirements

- Device with one free SMA or RP-SMA port

### Package content

- Adapter

### Item no. 89965

EAN: 4043619899654

Country of origin: Taiwan, Republic of China

Package: Poly bag

**Interface**

Connector 1:	<b>standard</b> 1 x SMA jack
Connector 2:	<b>standard</b> 1 x RP-SMA jack 90°

**Technical characteristics**

Frequency range:	<b>standard</b> 3 GHz
Operating temperature:	<b>standard</b> -10 °C ~ 50 °C

**Physical characteristics**

Housing material:	<b>standard</b> Brass gold plated
Length:	<b>standard</b> 15.15 mm
Width:	<b>standard</b> 15.15 mm
Thread type:	<b>standard</b> 1/4" - 36 UNS - 2A