

Suspended Ceiling Projector System with 2-Gang Filter & Surge - SYSAUBP2 **SKU: SYSAUBP2**



Designed for speed and flexibility from an ordering and installation standpoint. Chief's SYSAU Suspended Ceiling Projector System cuts installation time by one-third and includes everything needed to complete the majority of installations.

Output: 15A, 1875 W continuous

Power Requirements:

- N-G; 800V L-G Maximum Continuous Operating Voltage (MCOV): 240V Nominal Discharge Current (In): 3kA Short Circuit Current Rating (SCCR): 5kA Ambient Temperature Max: 40 degrees C
- Power Consumption: >0.5 watt Type 3 Surge Protective Device (SPD) Voltage Protection Rating (VPR): 600V L-N

Specifications

Dimensions &

Measurements

Depth	63.35 cm (24.9 in)
Height	50.34 cm (19.8 in)
Overall Dimensions	19.82" x 7.25" x 24.94" (503.5 x 184.2 x 633.6 mm)
Shipping Weight	11.34 kg (25 lbs)
Weight Capacity	35 lbs (15.9 kg)
Width	18.42 cm (7.3 in)

Characteristics &

Features

Adjustability	<ul style="list-style-type: none">• Independent Roll-Pitch-Yaw• Micro-Adjustable
Adjustments	<ul style="list-style-type: none">• Pitch 10°• Roll: 3°• Yaw: 360°
Application	Ceiling
Color	Black
Solution Type	Universal
Special Features	Kits, Surge and Filtering
TAA Compliant	No
UPC	841872167152

Certifications &

Warranties

Certifications	UL Listed
----------------	-----------

Source: <https://www.legrandav.com/products/mounts/projector-mounts/universal-suspended-ceiling-mount-kits/sysaubp2>