

Product datasheet

Specifications



APC Service Bypass PDU, 230V 10AMP W/ (6) IEC C13

Local distributor code:

422503745

SBP1500RMI



EAN Code: 0731304263593

Main

| | |
|---------------------------|---------------------------------------|
| Main Input Voltage | 230 V |
| Product or component type | Bypass kit |
| Main Output Voltage | 230 V |
| Input Connection Type | IEC 60320 C14 |
| Number of rack unit | 2U |
| Cable length | 2.0 m |
| Number of cables | 1 |
| Provided equipment | User manual Rack mounting brackets |
| Range of product | Maintenance Bypass Panels |

Physical

| | |
|---------------------|---------------|
| Colour | Black |
| Height | 89 mm |
| Width | 432 mm |
| Depth | 76 mm |
| Product weight | 2 kg |
| Mounting location | Front |
| Mounting preference | No preference |
| Mounting mode | Rack-mounted |

Input

| | |
|----------------------|-------------|
| Network frequency | 50/60 Hz |
| permissible voltage | 220...240 V |
| Max line current | 10 A |
| Input current limits | 10 A |
| Load capacity | 1500 VA |
| Power factor | 0...1 |

Output

| | |
|--------------------------------|----------------------------------|
| Max current draw | 10 A |
| Number of power socket outlets | 6 IEC 60320 C13 1 IEC Jumpers |

| | |
|--------------------------------|-----------------|
| Number of power socket outlets | 6 |
| Protection type | Circuit breaker |
| Power cable length | 1.2 m |
| Efficiency | 99 % |

Conformance

| | |
|------------------------|--|
| Product certifications | VDE |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...15000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...15240 m |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.100 cm |
| Package 1 Width | 46.300 cm |
| Package 1 Length | 29.500 cm |
| Package 1 Weight | 3.490 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 56 |
| Package 2 Height | 111.000 cm |
| Package 2 Width | 120.000 cm |
| Package 2 Length | 100.000 cm |
| Package 2 Weight | 195.440 kg |

Logistical informations

| | |
|-------------------|----|
| Country of origin | IN |
|-------------------|----|

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| SCIP Number | 7a19864b-8bf5-40ac-85e8-7678b0910185 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture


| | |
|------------|---|
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative

