



SNE SERIES RACK, SNE30D-4548-P1

SNE30D-4548-P1 |

FEATURES & BENEFITS

The SNE Series Digital is configured for digital (IP based) security systems consisting of high-density cabling, network equipment, and servers. Optional Tool-Free Lever Lock™ system accommodates small devices including encoders, power supplies, and Access Control Systems. • Fully configured Security Network Enclosure with passive ventilation for data centers o 70% open area vented front door o Pair of split flush mount locking side panels o 2 pair of adjustable cage-nut rackrail (including 6mm hardware) o Lever Lock™ compatible (accepts all Lever Lock™ vertical 21" accessories) o 30" width o 48" overall depth o 45 rackspace o 100 6mm cage-nuts/rack screws included SNE Series Digital with passive cooling (front to rear) • 70% open area split rear door • Solid top with brush cable pass-through



- Lever Lock™ compatible (accepts all 21" vertical accessories)
- UTL/ETL listed and seismic certified
- Configured for passive front-to-back cooling
- Includes 70% open front door and 70% open area split rear door
- Includes solid top with brush cable pass-through
- Includes 2 pair of adjustable cage-nut rackrail
- Includes 100 6mm cage nuts and rack screws
- Includes 4 leveling feet
- Includes 4 casters

SPECIFICATIONS

GENERAL INFO

Gangable: Yes
Finish: Black Powder Coat
UL Standards Tested: UL2416
Component Type: Passive

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

Greenguard: Yes
ETL Listed: Yes
UL Listing No: E313734
UL Standard: Yes

DIMENSIONS

Usable Depth: 44.48
Usable Height: 78.75
Panel Width: 19
Capacity Weight (US): 12000
Depth (US): 49.15
Height (US): 84.77
Width (US): 30
Rack Units: 45

TECHNICAL INFORMATION

Rackrail Type: Cage Nut
Static Load Capacity: 12000
UL Load Capacity: 3000
Material: Steel
Mounting: Horizontal
Seismic Rating: Yes