



Multi-format Conference Table Switch

No.: 38269

Automatic switching of HDMI, Mini-DisplayPort, VGA and Type C Alt Mode

Description

- Easily switch between both digital and analogue source devices
- Converts and scales signals to a HDMI output
- HDMI, Mini DP, VGA, 3.5mm Audio and USB Type C input ports
- Can be fixed securely inside a table or podium for a more discreet installation
- 2 Year Warranty

The Lindy Multi-format conference table switch is a premium design, multi-function solution for providing hassle-free control over multiple digital and analogue source devices when connected to a single HDMI display or projector, while also ensuring the maximum possible resolution is shown using automatic conversion and scaling to HDMI. The switch can mounted securely inside a conference table or podium with a high quality metal cover for a more discreet installation, while allowing simple access for connecting multiple devices, providing a perfect addition to any collaborative meeting room or live presentation podium.

Supporting resolutions up to 4K 60Hz 4:4:4 8bit, content can be viewed in crystal clear 4K Ultra HD quality, perfect for viewing engaging presentations, high-res design content or detailed spreadsheets, while the unit's scaling capabilities ensure whether a digital signal, from a HDMI Blu-ray player or mDP laptop, or an analogue signal, from a VGA compatible PC, is connected, the highest possible resolution is displayed with issue free playback. The switch also features two simple methods for control between multiple AV source devices, either by a manual push button on the unit or via auto-switching, which will automatically switch to the last active signal.

For added convenience the switch also features an Ethernet port and a USB charging Type C port, ideal for use in the absence of Wi-Fi or for powering mobile devices and some laptops.

Technical details

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 2.0
- Supports Bandwidth: 18Gbps
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
- HDCP Support: 2.2
- Supported Audio: Audio Pass-through
- Separate Audio Ports: Stereo (3.5mm)
- IR Support: -

- CEC Support: Pass-Through
- Serial Interface: -
- Special Features: EDID Bypass, Ethernet Pass-through

Connectors

- Input:
 - HDMI (Female)
 - Mini-DP (Female)
 - VGA (Female)
 - 3.5mm (Female)
 - USB Type C (Female)
 - RJ-45 (Female)
- Output:
 - HDMI (Female)
 - RJ-45 (Female)
- Control: Push Button
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions (approx.) WxDxH: 184x90x80mm (7.24x3.54x3.15in)
- Housing Material: Metal
- Net Weight: 0.737kg (1.62lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 0 – 60% RH (non-condensing)
- Power Requirements: 5VDC 3A
- Colour: Black

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 248x95x195mm (9.76x3.74x7.68in)
- Gross Weight: 1.1kg (2.43lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- Multi-Format Presentation Switch
- 2x Table mount hooks with screws
- Multi-Country Power Supply (EU, UK, AUS & USA)
- LINDY Manual

Purchasing Information

- No.: 38269
- EAN: 4002888382694