

# Product datasheet

Specifications



## NetShelter SX 12U 600mm Wide Perforated Curved Door Black

AR7060

EAN Code: 0731304347729

### Main

|                           |   |
|---------------------------|---|
| Product or component type | Door  |
| Provided equipment        | Door handle<br>Door mounting hardware<br>Installation guide<br>Key(s) |

### Physical

|                     |                     |
|---------------------|---------------------|
| Colour              | Black               |
| Height              | 730 mm              |
| Width               | 755 mm              |
| Depth               | 150 mm              |
| Product weight      | 7.5 kg              |
| Mounting preference | No preference       |
| Mounting mode       | Not rack-mountable  |
| Marking             | 16 gauge front door |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 15 cm   |
| Package 1 Width              | 75.5 cm |
| Package 1 Length             | 73 cm   |
| Package 1 Weight             | 7.5 kg  |

### Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|  |   |
|--|---|
| Total lifecycle Carbon footprint                       | 26 kg CO2 eq.                                 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 25 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 0.6 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.6 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|  |   |
|--|---|
| Packaging made with recycled cardboard | No  |
| Packaging without single use plastic   | No  |
| EU RoHS Directive                      | <a href="#">Compliant</a>   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |  |
|---------------------------------|--|
| Recyclability potential, in %   | 95                                       |
| End of life manual availability | No need of specific recycling operations |
| Take-back                       | No                                       |