

# Delock CFexpress memory card 128 GB

## Description

This flash module by Delock is a memory in CFexpress 1.0 (CFX) type B format. The memory card is particularly suitable for photo and video applications, as the PCI Express standard allows large data to be exchanged very fast. In addition, the PCIe resp. NVMe standard and the low latencies make the card suitable for industrial applications in which removable storage media are required.



128 GB

**Item no. 54065**

EAN: 4043619540655

Country of origin: Taiwan,  
Republic of China

Package: Antistatic cover

## Specification

- Connector:  
1 x CFexpress 1.0
- Capacity: 128 GB
- Interface: PCIe x2 Rev. 3.0
- Form factor: type B
- Flash type: TLC
- Maximum read speed: 1450 MB/s
- Maximum write speed: 450 MB/s
- MTBF: 1.500.000 hours
- Power consumption: max. 2.6 W
- Vibration: 20G
- Shock: 1500G
- Storage temperature: -40 °C ~ 85 °C
- Operating temperature: 0 °C ~ 70 °C
- Supports NVM Express (NVMe)
- Supports TRIM
- Supports S.M.A.R.T.
- Dimensions (LxWxH): ca. 38.5 x 29.6 x 3.8 mm

## System requirements

- A free CFexpress slot
- 

## Package content

- CFexpress memory card
- 

## Images



## Interface

connector:	1 x CFexpress 1.0
------------	-------------------

## Technical characteristics

Operating temperature:	0° C - 70° C
Storage temperature:	-40 °C ~ 85 °C
Read:	1450 MB/s
Maximum power consumption:	2.6 W
MTBF:	1.500.000 hours
Interface:	PCI Express
Shock:	1500 G
Write:	450 MB/s
Capacity:	128 GB
Vibration:	20 G