

Vertical IEC (C13) PDUs



Vertical IEC PDU

Picture shows IEC16V

IEC C20 plug



- 10A IEC C13 60320(320) sockets
- Tough aluminium extrusion
- Shrouded switch and switch cover
- C14, C20, or 16A commando options
- 3m 1.5mm cable

Vertical IEC PDUs are widely used to accommodate cabinets where a higher number of IEC sockets are needed, but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical hardware.

Standard products

Order Code

Product Description

IEC6VC20	6-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug
IEC8VC20	8-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug
IEC10VC20	10-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug
IEC12VC20	12-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug
IEC16VC20	16-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug
IEC20VC20	20-way IEC C13 10A power with switch to 3-metre lead to IEC C20 plug


PDU options



IEC C14 plug
IEC 60320(320)



16A commando plug
IEC 60309(309)



IEC C20 plug
IEC 60320(320)

PDU technical data

Weight of PDU	1.15kg – 1.5kg
Net length of PDU	IEC6/IEC8/IEC10/IEC12 : 490mm IEC16: 590mm IEC20: 700mm
Net width of PDU	60mm
Net depth of PDU	45mm
Shipping length of PDU	520mm – 825mm
Shipping Width of PDU	132mm
Shipping Depth of PDU	75mm
Shipping Weight of PDU	1.3kg – 1.85kg
PDU max power	3250W
Output rating	C13: 10A
Overall rating	16A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC

