



## Vertical UK PDU

Picture shows PDU10V16A

16A Commando plug



- Vertical UK BS1363 right-angled outlets
- Tough aluminium extrusion
- Shrouded switch and switch cover
- C14, C20, or 16A commando options
- 3m 1.5mm cable

Vertical UK PDUs are widely used to accommodate cabinets where a higher number of UK sockets are needed, but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical hardware.

### Standard products

Order Code

Product Description

|           |                                                                      |
|-----------|----------------------------------------------------------------------|
| PDU4V16A  | 4-way UK 13A power with switch to 3-metre lead to 16A Commando Plug  |
| PDU5V16A  | 5-way UK 13A power with switch to 3-metre lead to 16A Commando Plug  |
| PDU6V16A  | 6-way UK 13A power with switch to 3-metre lead to 16A Commando Plug  |
| PDU8V16A  | 8-way UK 13A power with switch to 3-metre lead to 16A Commando Plug  |
| PDU10V16A | 10-way UK 13A power with switch to 3-metre lead to 16A Commando Plug |
| PDU12V16A | 12-way UK 13A power with switch to 3-metre lead to 16A Commando Plug |
| PDU16V16A | 16-way UK 13A power with switch to 3-metre lead to 16A Commando Plug |


### PDU options



IEC C14 plug  
IEC 60320(320)



16A commando plug  
IEC 60309(309)



IEC C20 plug  
IEC 60320(320)

### PDU technical data

|                          |                |
|--------------------------|----------------|
| Weight of PDU            | 0.95kg – 1.9kg |
| Net length of PDU        | 490mm – 1090mm |
| Net width of PDU         | 60mm           |
| Net depth of PDU         | 45mm           |
| Shipping length of PDU   | 515mm – 1120mm |
| Shipping Width of PDU    | 150mm          |
| Shipping Depth of PDU    | 70mm           |
| Shipping Weight of PDU   | 1.1kg – 2.4kg  |
| PDU max power            | 3250W          |
| Output rating            | 13A            |
| Overall rating           | 16A            |
| Input Frequency          | 50/60Hz        |
| Acceptable Input Voltage | 250VAC         |

