



# Delock 4 port SATA and 1 slot M.2 Key B PCI Express x4 Card -Low Profile Form Factor

### Description

The PCI Express card by Delock expands a PC by four internal **SATA** ports and one **M.2** slot. Different devices such as SSDs, hard drives, DVD-drives etc. and one M.2 module in 2242 or 2230 format can be connected to the card.



### ltem no. 90396

EAN: 4043619903962

Country of origin: China

Package: Retail Box



# Specification

# Connectors: internal:

- 4 x SATA 6 Gb/s 7 pin plug 1 x 67 pin M.2 key B slot
- 1 x PCI Express x4, V3.0
- Chipset: JMicron JMB585
- 5 x LED indicator
- Interface: SATA
- Supports M.2 modules in format 2242 and 2230 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports Native Command Queuing (NCQ)
- Supports S.M.A.R.T.
- Supports TRIM
- Supports DevSleep
- Hot Swap
- Bootable

#### System requirements

- Linux Kernel 3.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

### Package content

- PCI Express card
- Low profile bracket
- 4 x SATA cable, length ca. 50 cm
- M.2 mounting material
- User manual






# Images















| General                     |   |
|-----------------------------|---|
| Function:                   | Hot Swap  |
|                             | bootable  |
| Supported operating system: | Windows 7 32-bit  |
|                             | Windows 7 64-bit  |
|                             | Windows 8.1 32-bit  |
|                             | Windows 8.1 64-bit  |
|                             | Windows 10 32-bit   |
|                             | Windows 10 64-bit   |
|                             | Linux Kernel 3.3 or above   |
| LED indicator:              | 5 x   |
| Supported module:           | M.2 modules in format 2242 and 2230 with key B or key B+M based on SATA |
| Interface                   |   |
| Internal:                   | 1 x PCI Express x4, V3.0  |
|                             | 1 x 67 pin M.2 key B slot   |
|                             | 4 x SATA 6 Gb/s 7 pin plug  |
| Technical characteristics   |   |
| Chipset:                    | JMicron JMB585  |
| Data transfer rate:         | 6 Gb/s  |