

# Universal DC Power Adapter for Industrial USB Hubs - 20V, 3.25A

Product ID: ITB20D3250



This universal DC power adapter has been designed as an alternative, back up or replacement power supply for StarTech.com's line of industrial USB hubs.

## Compatible USB 3.0 Hubs

10-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A10AME](#))

10-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST1030USBM](#))

7-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A7AME](#))

7-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST7300USBME](#))

4-Port Industrial USB 3.0 Hub with ESD Protection ([ST4300USBM](#)ST4300USBM)

**Compatible USB 2.0 Hubs:**

7-Port Industrial USB 2.0 Hub ESD Protection & 350W Surge Protection (HB20A7AME)

7-Port Industrial USB 2.0 Hub with ESD & 350W Surge Protection (ST7200USBM)

4-Port Industrial USB 2.0 Hub with ESD Protection & 350W Surge Protection (HB20A4AME)

4-Port Industrial USB 2.0 Hub with ESD Protection (ST4200USBM)

The external terminal power adapter can also be used with any other devices that can support 20V power supply including a variety of StarTech.com Ethernet Switches and Serial Adapters.

The ITB20D3250 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Features

- Terminal block power adapter has been designed for StarTech.com industrial products
- Use as an alternative power source, replacement, or back-up power supply when sufficient bus-power is unavailable
- Includes regional plug attachments for NA/JP, EU, UK & ANZ
- Includes an attached two conductor terminal block
- Includes an additional three conductor terminal block

|                                 |                           |                                                       |
|---------------------------------|---------------------------|-------------------------------------------------------|
| <b>Power</b>                    | Warranty                  | 1 Year                                                |
|                                 | Input Current             | 1.4A Max.                                             |
|                                 | Input Voltage             | 110V-240V AC                                          |
|                                 | Output Current            | 3.25A                                                 |
|                                 | Output Voltage            | 20V DC                                                |
|                                 | Plug Type                 | Terminal Block (2 Wire)                               |
|                                 |                           | Terminal Block (3 Wire)                               |
| Power Consumption (In Watts)    | 65W                       |                                                       |
| <b>Environmental</b>            | Humidity                  | 20% ~ 80% RH                                          |
|                                 | Operating Temperature     | + 0°C ~ + 40°C                                        |
|                                 | Storage Temperature       | - 20 °C ~ + 80°C                                      |
| <b>Physical Characteristics</b> | Product Height            | 0.000                                                 |
|                                 | Product Length            | 0.000                                                 |
|                                 | Product Width             | 0.000                                                 |
|                                 | Weight of Product         | 0.000                                                 |
| <b>Packaging Information</b>    | Package Height            | 55.000                                                |
|                                 | Package Length            | 166.000                                               |
|                                 | Package Width             | 242.000                                               |
|                                 | Shipping (Package) Weight | 810.000                                               |
| <b>What's in the Box</b>        | Included in Package       | 1 - Universal 65W Power Adapter                       |
|                                 |                           | 4 - Power Cords (NA/JP, EU, UK, ANZ)                  |
|                                 |                           | 1 - Two Conductor Terminal Block Connector (Attached) |
|                                 |                           | 1 - Three Conductor Terminal Block Connector          |
|                                 |                           | 1 - Quick Start Guide                                 |

Product appearance and specifications are subject to change without notice.