

# Delock USB Type-C™ Adapter to HDMI 4K 30 Hz with USB Type-A and USB Type-C™ PD

## Description

This adapter by Delock is suitable for the connection of a **HDMI monitor** to a computer with **USB-C™** interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.

## USB Power Delivery (USB PD 2.0) support up to 60 watt

The adapter has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it.



4K  
30Hz

## Note

When used on a smartphone, an additional power supply may be required if the monitor output and a USB memory device are connected at the same time.

## Specification

- Connectors:
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male >
  - 1 x HDMI-A 19 pin female
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female - Battery Charging specification BC1.2
  - 1 x USB Type-C™ Power Delivery female (optional for power supply)
- Chipset: Algotek AG6310
- DisplayPort 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Input power: 1 x USB Type-C™ female max. 60 W
- Supports 3D displays
- Supports HDCP 1.4
- USB bus powered
- Plug & Play
- Cable length without connectors: ca. 15 cm
- Colour: black

## System requirements

- Android 8.0 or above
- Chrome OS 75.0 or above
- Mac OS 10.14.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- USB-C™ to HDMI Adapter + USB Type-A

## Item no. 64091

EAN: 4043619640911

Country of origin: China

Package: Retail Box



Images



General	
Function:	Plug & Play
Specification:	High Speed HDMI with Ethernet HDCP 1.4
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Android 8.0 or above Chrome OS 75.0 or above Mac OS 10.14.6 or above
Interface	
Connector 1:	1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male
Connector 2:	1 x HDMI-A 19 pin female
connector 3:	1 x USB Type-C™ Power Delivery female
connector 4:	1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female - Battery Charging specification BC1.2
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio
Physical characteristics	
Housing material:	Plastic
Cable length:	15 cm