

# Delock USB Type-C™ DP 1.4 Docking Station 4K - HDMI / DP 1.4 / USB 3.2 / LAN / PD 3.0

## Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Up to three monitors can be operated simultaneously at the **DisplayPort** and **HDMI** outputs. Four built-in **USB ports** allow the use of peripherals, and connections for **headset** and **Gigabit network** complete the features.

### Multi-Stream Transport (MST)

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows **multiple monitors** to be combined into one large display. The maximum resolution for simultaneous playback on two or three monitors depends on the system and connected hardware.

### USB Power Delivery (USB PD 3.0) support up to 85 watt

The docking station has a USB Type-C™ Power Delivery port. If this port is connected to the host device, such as the MacBook, it will charge up to **85 watts** during operation.

### Stand, security and VESA mounting

The Delock docking station can be operated either **horizontally or vertically**. A stand is included for vertical operation. Further the docking station can also be mounted to a **50 mm VESA bracket**. The corresponding screw threads are provided on the bottom for this purpose. A safety cable can be attached to the **Kensington socket** to protect the docking station from theft.



## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female >
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-A female - Battery Charging specification BC1.2
  - 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
  - 1 x HDMI-A female
  - 2 x DisplayPort female
  - 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
  - 1 x Headset 3.5 mm 4 pin jack
  - 1 x DC jack
- Maximum resolution (depending on the system and the connected hardware):
  - DisplayPort 1.4 Multi-Stream Transport (MST):
  - 1 display: up to 3840 x 2160 @ 60 Hz
  - 2 or 3 displays: up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Functions: Mirrored or Extended, with Mac OS and Chrome only one monitor can be extended, all others are mirrored
- Supports HDCP 1.4
- Supports HDR
- Output power for host: max. 85 W
- 1 x On / Off switch
- 1 x LED indicator
- Security lock (Kensington Lock) for security cable
- Screw thread for 50 mm VESA holder

Item no. 87746

EAN: 4043619877461

Country of origin: China

Package: Retail Box





- Colour: black
- Dimensions (LxWxH): ca. 190 x 85 x 27 mm

#### Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.8 A
- Output: 20 V / 6.75 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 5.0 mm
  - outside: ø ca. 7.5 mm
  - length: ca. 12 mm

#### System requirements

- Chrome OS
- Mac OS 10.14.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

#### Package content

- USB-C™ docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- Power supply
- User manual

#### Images





## General

Supported operating system:	Chrome OS
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 Mobile
	Mac OS 10.14.5 or above

## Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
----------------------------	---------------------

## Physical characteristics

Length:	190 mm
Width:	85 mm
Height:	27 mm
Colour:	black