

Mercodan CAT6A UTP Ultra Thin Patchcord AWG28

Features

- ULTRA SLIM CABLE OD=3.8mm, High Performance Cat6a, 28 AWG,RJ45, unshielded Ethernet Cable Very convenient for traveling.
- Upload & Download Speed - Support Bandwidth Up To 500MHz & Transmitting data at speeds of up to 10Gbps ,Connect To LAN/WAN Segments And Networking Gear At Maximum Speeds.
- Provides universal connectivity for LAN network components such as PCs, computer servers, printers, routers, switch boxes, network media players, NAS, VoIP phones, PoE devices, and more.
- The extra performance is ideal for Power over Ethernet (PoE) and Voice Over Internet Protocol (VoIP) applications where data loss is audibly and visually seen and heard.

Packaging

Varenummer	COFERRO	LENGTH	OUTER CARTON		
			Q'ty/Carton	L x W x H	G.W./Carton
37192x002		0.25m	500pcs	42.5*30*22cm	
37192x005		0.5m	400pcs	42.5*30*22cm	
37192x010		1.0m	200pcs	42.5*30*22cm	
37192x015		1.5m	160pcs	42.5*30*22cm	
37192x020		2.0m	140pcs	42.5*30*22cm	
37192x030		3.0m	100pcs	42.5*30*22cm	
37192x050		5.0m	70pcs	42.5*30*22cm	
37192x075		7.5m	50pcs	42.5*30*22cm	
37192x100		10m	40pcs	42.5*30*22cm	
37192x150		15m	30pcs	42.5*30*22cm	
37192x200		20m	20pcs	42.5*30*22cm	



Specifications

- CONNECTOR 1 : CAT 6A UTP RJ45-8P8C PLUG , G/F .
- CONNECTOR 2: CAT 6A UTP RJ45-8P8C PLUG , G/F.
- Wire : UTP 4pair Twisted 28AWG-CU , LSZH Jacket , OD3.8MM.
- Support PoE,Fluke testet
- Length: 0.25-20m .

Packaging Image



NOTE:

- 1.100% electrical performance test
Parameter Settings: CT-8681FA
a. Insulation Resistance:5MΩ (MIN).
b. Conductive Resistance:2.0Ω (MAX).
- 2.Packing: Bulk Packing

REV.	Description	Date
A		
B		10-2019

XXX±20MM



SIDE:A		SIDE:B
8P8C		8P8C
1	WHITE/ORANGE	1
2	ORANGE	2
3	WHITE/GREEN	3
6	GREEN	6
4	BLUE	4
5	WHITE/BLUE	5
7	WHITE/BROWN	7
8	BROWN	8

PIN OUT

③	MOLDED	TPE	1	PCS
②	CONN	RJ 45,8P8C,UTP CAT.6A,TRANSPARENT,PIN GOLD PLATED FU" TPE	2	PCS
①	CABLE	UTP CAT.6A (1P*7/0.12BC)*4C,JACKET:LSZH ,OD:3.8±0.2MM	XXX	MM
NO.	MATERIAL	DESCRIPTION	QTY	UNIT

Item Number				Drawer	Cheryl Cao
Description	CAT6A UTP Ultra Thin Patchcord AWG28			Checked	Emil Olsen
Material		Scale	1:1	Approved	Emil Olsen
	A	Unit	MM		
					
Cufomer No:				MERCODAN COFERRO CABLES	
Remark	ROHS Compliant				