



## QSW-M408-4C

Management Type	Web Managed
Fan	PWM double ball bearing fan x 1
Jumbo Frames	9K
Electromagnetic Compliance	CLASS A
Certifications	CE, FCC, VCCI, BSMI
Relative Humidity	5~95% Non-condensing
Operating Temperature	0°C to 45°C (32°F to 113°F)
Weight (Gross)	1.57 kg
Weight (Net)	1.15 kg
Dimensions (HxWxD)	42.5 × 290 × 127 mm
Buttons	Reset button
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Form Factor	Desktop
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3bz 2.5G/5GBase-T IEEE 802.3an 10G BASE-T IEEE 802.3z 1000BASE-SX/LX IEEE 802.3ae 10G Fiber IEEE 802.3x Full-Duplex Flow Control IEEE 802.1Q VLAN Tagging IEEE 802.1w RSTP IEEE 802.3ad LACP IEEE 802.1AB LLDP IEEE 802.3az Energy Efficient Ethernet IEEE 802.1p Class of Service
Sound Level	< 21

Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Number of Ports	12
Console (Opt.)	RJ45
Management Interface	Web
Switching Capacity	96Gbps
Total Non-Blocking Throughput	48Gbps
MAC Address Table	16K
Input Voltage Range	100-240VAC, 50/60 Hz
Input Power Type	AC
Max. Power Consumption	31.46 W
Power Supply Description	Adapter
1GbE (RJ45)	8
10GbE SFP+/RJ45 Combo Ports	4
Warranty	2 Years