

PRODUCT DATASHEET

LEDstixx

LEDstixx | Little helpers



AREAS OF APPLICATION

- Sideboards
- Flower arrangements
- Practical adhesive surface or drill holes
- Horizontal or vertical alignment on walls or objects

PRODUCT BENEFITS

- Very compact LED luminaire

PRODUCT FEATURES

- Modern luminaire
- High-quality aluminum casing



TECHNICAL DATA


Electrical data

Nominal wattage	0.6 W
Operating mode	Battery
Nominal voltage	4.5 V

Photometrical data

Color temperature	6200 K
Color rendering index Ra	≥80
Luminous flux	25 lm

Dimensions & weight



Length	222.0 mm
Width	16.2 mm
Diameter	16.2 mm
Height	22.0 mm
Product weight	94.00 g

Colors & materials

Body material	Aluminum
Housing color	Silver
Product color	Silver

Temperatures & operating conditions

Ambient temperature range	0...+25 °C
---------------------------	------------

Lifespan

Lifespan	10000 h
----------	---------

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
LED module replaceable	Not replaceable
With on/off switch	Yes

Certificates & standards

Protection class	III
Type of protection	IP20
Standards	CE

COUNTRY SPECIFIC INFORMATION

Product code	METEL code	SEG-No.	STK number	UK Org
4008321951236	OSRLEDSTIXX	-	8773314	-

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321951236	Role 1	72 mm x 72 mm x 280 mm	171.00 g	1.45 dm ³
4008321951243	Shipping carton box 6	230 mm x 160 mm x 283 mm	1297.00 g	10.41 dm ³
4008321955722	Shipping carton box 24	537 mm x 317 mm x 283 mm	6128.00 g	48.17 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.