

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: UI10026

Model Number: DU01X1R1-12CF17-1S02A9H00-S

Category: Basic

Sub Category: Upgradeable

Power Configuration: Variable, Variable, 11.0kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Basic Upgradeable, Max 11.0kW, Variable Power Configuration, Vertical, (12) Combination C13/C19, Universal Input, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



Universal Inlet

Receptacle:



Combination C13/C19
(Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring

No Monitoring (Upgradeable with IMD module)

| | |
|--|---|
| Maximum Input Power (Defined by Facility Side Cable) | 48A Single Phase, 240V Max, 11.0kW 24A 3 Phase DELTA, 240V Max, 8.6kW 16A Three Phase WYE, 240/415V Max, 11.0kW |
| Frequency | 50/60Hz |
| Over Current Protection | (3) 16A Double Pole Magnetic Breakers (10kAIC Rated) |
| Switch | Breaker/Switch Combination |
| Power Entry Location | Left Rear |
| Plug Type | Universal Inlet |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Face | 12 |
| - Quantity per Breaker | 4 |
| - Circuit Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | Defined by Facility Side Cable |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 1U |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | FCC Part 15 Class A Conformance |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | UL Listed 60950 |
| Chassis Dimensions (HxWxD) | 1.72in x 17in x 9in / 44mm x 432mm x 229mm |
| Shipped Weight | 21lbs (9.53kg) |