





SHELL _____ SHELL

④	MOLDED	BLACK 45P PVC	0.021	KG
③	CONNECTOR	MINI USB B TYPE MALE,BLACK INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	USB A TYPE MALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	USB2.0 1P*28#+2C*28#+AB OD:3.9±0.1 JACKET:BLACK PVC MARKING:AWM STYLE 2725 80V 30V VW-1 USB2.0 High Speed Cable-ROHS	2	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

2:Insulation resistance:DC300V 10MΩ(Min)
Conduction resistance 5Ω(Max)

REQUIREMENTS:

1:100% short,open and miss wire test.

Ltemref	Quantity	Title/Name,designation,material,dimension etc			Article No./Reference	
Designed by ACHY		Checked by HELEN	Approved by - date MARCH 6,2012	File name USB AM TO MINI BM L=2H	Date MARCH 6,2012	Scale FREE
32 3078						
32 3078					Edition 1	Sheet 1/1