

Delock USB Condenser Microphone Omnidirectional for Conferences

Description

This table microphone by Delock is suitable for use in conferences.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Touch mute button & status LED

The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

Headphone output

The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED

- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images



General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	1 x

Interface

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

Technical characteristics

Frequency range:	100 Hz - 10 kHz
Voltage:	USB bus powered
Sensibility:	-16 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. 65 dB
Directivity:	omnidirectional

Physical characteristics

Cable length:	1.5 m
Diameter:	75 mm
Height:	19 mm
LED colour:	red green

