

Delock Active DisplayPort 1.2 to HDMI Cable 4K 60 Hz 10 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.

Active cable

The cable offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.



Item no. 85960

EAN: 4043619859603

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x DisplayPort male >
 - 1 x HDMI-A male
- Signal direction: DisplayPort input > HDMI output
- Chipset: Parade PS176
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- Contacts gold-plated
- Active cable, for graphics cards with DP and DP++ output
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Colour: black
- Dimensions of signal amplifier (LxWxH): ca. 8.00 x 2.20 x 1.35 cm

- Length incl. connectors: ca. 10 m
-

System requirements

- A free DisplayPort female
-

Package content

- DisplayPort to HDMI cable
-

Images



General

| | |
|----------------|------------------------------------|
| Specification: | DisplayPort 1.2 High Speed HDMI |
|----------------|------------------------------------|

Interface

| | |
|--------------|----------------------|
| Connector 1: | 1 x DisplayPort male |
| Connector 2: | 1 x HDMI-A male |

Technical characteristics

| | |
|----------------------------|---------------------|
| Chipset: | Parade PS176 |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |

Physical characteristics

| | |
|---------------------|-------------|
| Ferrite core: | 2 x |
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 28 AWG |
| Shielding: | triple |
| Diameter: | 7.2 mm |
| Length: | 10 m |
| Colour: | black |