



## 3m USB Type C to DisplayPort 4K60 Adapter Cable with HDR

No.: 43303

Connect a DP display to your computer's USB Type C port

### Description

- Connects a 4K DP display to a computer equipped with a USB Type C port
- Supports DisplayPort resolutions up to 4K 3840x2160@60Hz with HDR
- Perfect for connecting Macbooks, laptops and PCs to modern DP displays
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- 2 year warranty

Lindy USB Type C to DisplayPort 4K60 Adapter Cable with HDR allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. This DisplayPort connector of the adapter cable can be directly connected to the DisplayPort display with the 3m cable allowing for additional flexibility when positioning of the DP display - perfect for a simple and adaptable installation.

With support for resolutions up to 3840x2160@60Hz and with additional support for High Dynamic Range, 4K content can be viewed with crystal clear clarity, enhanced contrast and more lifelike colour. These cables are great for creating eye-catching retail displays, innovative working environments or immersive video playback in sports bars and home cinema installations, while support for uncompressed multi-channel audio allows for an impressive three-dimensional surround sound performance to compliment detailed, clear video.

This cable is powered by the USB Bus, so no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV system with minimum difficulty, ideal for both professional and first time users.

### Technical details

#### Connectors

- Connector A: USB Type C Male
- Connector B: DisplayPort Male
- Housing Material: USB C: PVC, DP: ABS shell
- Connector Plating: Gold plating
- Pin Construction: Copper alloy
- Pin Plating: Gold plating
- Dimensions (approx.) WxDxH:

- USB: 32x12x6.3mm (1.26x0.47x0.25in)
- DP: 47.17x21.8x9.2mm (1.86x0.86x0.36in)

**Cable construction**

- Length: 3m (9.84ft)
- Standard: DP 1.2
- Colour: Black
- Type: Round
- Jacket Diameter: 4.5mm (0.18in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 32AWG
- Shielding: Copper Braid 85%

**Specifications**

- Chipset: VL100
- Supported Bandwidth: 21.6Gbps
- Power Delivery: -
- Maximum Resolution: 3840x2160@60Hz 10bit 4:4:4
- Nominal Attenuation: 0.1MHz-6MHz<12DB
- Minimum Bend Radius: 47mm (1.85in)
- Operating Temperature: 0°C - 35°C (32°F - 95°F)
- Storage Temperature: 0°C - 45°C (32°F - 113°F)

**Miscellaneous**

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, California Proposition 65

**Purchasing information**

- No.: 43303
- EAN: 4002888433037

**This product is also available in other lengths**

- 43301 - 1m (3.28ft)
- 43302 - 2m (6.56ft)
- 43303 - 3m (9.84ft)