

Product datasheet

Specifications

APC Symmetra PX 9Ah Battery Unit, High Performance



SYBTU2-PLP

Overview

Presentation	For Symmetra PX 100, it is recommended to replace all four batteries in a row at the same time to ensure optimal runtime. If you are ordering this battery unit for a Symmetra PX 100, you must order battery units in multiples of 2 and you must replace string positions A+B or C+D, as the batteries are connected in pairs. The batteries in each half string must be from the same manufacturer. For Symmetra PX 250/500, it is recommended to replace all six batteries in a row at the same time to ensure optimal runtime. If you are ordering this battery unit for a Symmetra PX 250/500, you must order battery units in multiples of 3 and you must replace the batteries in string position A+B+C or D+E+F, as they are connected in pairs. The batteries in each half string must be from the same manufacturer.
---------------------	---

Main

Provided equipment	Installation guide
---------------------------	--------------------

Physical

Colour	Black
Height	15.9 cm
Width	10.7 cm
Depth	70 cm
Product weight	25.2 kg
Mounting mode	Not rack-mountable
USB compatible	No

Conformance

Product certifications	CE
Standards	UL 1778

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...4572 m

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	18.000 cm
Package 1 Length	83.000 cm
Package 1 Weight	26.540 kg
Unit Type of Package 2	P12
Number of Units in Package 2	16
Package 2 Height	90.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	436.640 kg

Logistical informations

Country of origin	PH
--------------------------	----

Contractual warranty

Warranty (in months)	12
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative

