

Synology RMA Visual Inspection Procedures



Table of Contents

Chapter 1: Purpose	01
Chapter 2: Criteria For Acceptance	02
Packaging	
Product labels	
Chapter 3: Criteria For Denial	03
Packaging	
Product labels	
Top cover	
Connector	
Base	
Media	
Printed Circuit Board Assembly (PCBA)	
Other	
Chapter 4: Appendix	13
Packing and shipping instructions	

Purpose

The information provided in this document applies to Synology storage drives. Any Synology storage drives requiring a return merchandise authorization (RMA) must be returned in the same condition as it was received from Synology. The following chapters will explain the criteria for RMA denial and acceptance.

Note:

• All images in this document are for illustrative purposes only. The layout of your product may differ from that in the figures provided.

/ Criteria For Acceptance

Packaging

More proper packing and shipping instructions is available in the <u>appendix section</u>.

Use an ESD bag / clamshell to prevent electrostatic discharge (ESD) with additional material such as bubble wrap / EPE material for protection.



Product labels





Packaging





Product labels





A clear sticker should be covering the screw/hole.



Top cover



Deep and heavy scratches





Connector





Base





Media



Printed Circuit Board Assembly (PCBA)









Other





Packing and shipping instructions

Before shipping, please contact the local reseller or distributor where you purchased the product for an RMA number.

For single drive

- 1. Package the drive in an anti-static bag or similar material to prevent ESD.
- 2. Wrap the drive with bubble wrap or EPE material, then carefully place it in a box.
- 3. Do not use packing pellets, peanuts, air bags, or newspaper.
- 4. Make sure there are no free space in the box for the drive to shift around.
- 5. If necessary, insert the packing slip inside the package and seal the box with nylon or vinyl tape along all edges and openings.
- 6. Label should be placed on the outside of the package.





For multiple drives

- 1. Package each individual drive with an anti-static bag or similar material to prevent ESD.
- 2. Carefully place multiple drives into a box, with bubble wrap or EPE material in between each drive.
- 3. Do not use packing pellets, peanuts, air bags, or newspaper.
- 4. Make sure there are no free space in the box for the drives to shift around.
- 5. If necessary, insert the packing slip inside the package and seal the box with nylon or vinyl tape along all edges and openings.
- 6. Label should be placed on the outside of the package.







SYNOLOGY

INC. 9F, No. 1, Yuan Dong Rd. Banqiao, New Taipei 220632 Taiwan Tel: +886 2 2955 1814

SYNOLOGY AMERICA CORP.

3535 Factoria Blvd SE, Suite #200, Bellevue, WA 98006 USA Tel: +1 425 818 1587

SYNOLOGY UK LTD.

Unit 5 Danbury Court, Linford Wood, Milton Keynes, MK14 6PL, United Kingdom Tel.: +44 (0)1908048029

SYNOLOGY FRANCE SARL

102 Terrasse Boieldieu (TOUR W) 92800 Puteaux France Tel: +33 147 176288

SYNOLOGY <u>GM</u>BH

Grafenberger Allee 295 40237 Düsseldorf Deutschland Tel: +49 211 9666 9666

SYNOLOGY SHANGHAI

200070, Room 201, No. 511 Tianmu W. Rd., Jingan Dist., Shanghai, China

SYNOLOGY

JAPAN CO., LTD. 4F, No. 3-1-2, Higashikanda, Chiyoda-ku, Tokyo, 101-0031 Japan





synology.com

Synology may make changes to specifications and product descriptions at any time, without notice. Copyright © 2021 Synology Inc. All rights reserved. ® Synology and other names of Synology Products are proprietary marks or registered trademarks of Synology Inc. Other products and company names mentioned herein are trademarks of their respective holders.