



Delock 10" Industry Hub 10 x USB 3.2 Gen 1 Type-A

Description

This solid industry capable USB hub by Delock with metal housing can be connected to a computer via the USB Type-A interface. It expands the computer by 10 USB Type-A ports. The hub can be used for automation and office applications.

USB 3.2 Gen 1 specification

With the support of USB 3.2 Gen 1 specification a data transfer rate up to 5 Gbps can be reached. Compared to USB 2.0, data can be transferred 10 times faster. All ports are backward compatible, so USB 2.0 and USB 1.1 devices can be used as well.

10" rack mounting

With the supplied mounting brackets, the hub can be mounted in a 10" rack.



Specification

- · Connectors:
- 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-B female 10 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female 1 x 5 V DC jack $5.5 \times 2.1 \text{ mm}$
- Chipset: VIA VL813
- Data transfer rate up to:

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Output power: max. 16 W total
- · Robust metal housing
- Removable 10" rack brackets
- · LED indicator for power
- Operating temperature: 0 $^{\circ}$ C $^{\sim}$ 60 $^{\circ}$ C
- Dimensions (LxWxH): ca. 215 x 135 x 45 mm
- · Colour: black
- Plug & Play

Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.0 A
- Output: 5 V / 4 A
- · Ground outside, plus inside
- · Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements

- Linux Kernel 3.4 or above
- Windows 8.1/8.1-64/10/10-64
- · PC or laptop with a free USB Type-A port

Package content

- Hub USE
- 1 x cable USB 3.2 Gen 1 Type-A male to USB 3.2 Gen 1 Type-B male, length ca. 1.20 m
- 2 x mounting brackets for 10" rack
- Power supply
- User manual

Item no. 64112

EAN: 4043619641123

Country of origin: China

Package: • Box





Images









General	
Function:	Hot Swap
	Plug & Play
Mounting type:	10 in
Supported operating system:	Chrome OS
	Linux Kernel 3.3 or above
	Windows 10 64-bit
	Windows 7 64-bit
	Windows 8.1 64-bit
LED indicator:	Power
Interface	
Connector 1:	1 x USB 3.0 Type-B female
Connector 2:	10 x USB 3.0 Type-A female
connector 3:	1 x DC jack
Technical characteristics	
Data transfer rate:	USB 3.0 up to 5 Gb/s
Physical characteristics	
Length:	215 mm
Width:	135 mm
Height:	45 mm
Colour:	black
Power supply	
Type:	Euro wall power supply
Output:	5 V / 4 A
Connector:	DC male 5.5 mm x 2.1 mm