

Product datasheet

Specifications



Easy Rack PDU, Switched, 0U, 3 Phase, 11kW, 230V, 16A, 21 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet

EPDU1216S

⚠ To be discontinued

⚠ Discontinued on: 6 Jun 2025

⚠ To be end-of-service on: 31 Dec 2027

EAN Code: 0731304428022

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Number of cables	1
Provided equipment	Installation guide

Complementary

Input Voltage	400 V 3 phases
Height	1794 mm
Width	55 mm
Output Voltage	230 V
Depth	62 mm
Product weight	6.2 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P + N + PE
Mounting mode	Rack-mounted
Mounting position	Vertical
Input current limits	16 A
Load capacity	11 kW
Network frequency	50/60 Hz
Plug standard	IEC 60309
Outlet type and quantity	21 IEC 60320 C13 6 IEC 60320 C19

Environment

Product certifications	CE EAC RCM TÜV
------------------------	-------------------------

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.95 cm
Package 1 Width	16 cm
Package 1 Length	11 cm
Package 1 Weight	7.78 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	12
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	846 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	43 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	798 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins