SHARP/NEC

NEC MultiSync® ME501-MPi4

LCD 50" Midrange Large Format Display (incl. NEC MediaPlayer)

Datasheet





Digital Signage and real-time information deployed easily

Initiating effective communication to your target audience has never been easier to plan, install and operate. Deploying Signage with consistently updated information, real-time content adaption and scheduling has never been so simple.

The MultiSync® ME-MPi4 displays offer out-of-the-box playback for local retailers, restaurants and small business enterprises. With the NEC MediaPlayer you can deliver dynamic advertising and infotainment to your customers whilst benefiting from the efficiencies gleaned through digitisation.

Future-proof and upgradable, the NEC MediaPlayer software is powered by a pre-installed modular SoC Raspberry Pi module. Enabling remote operation of single and multiple display installations, benefit from flexible usage of many media types and a scheduling function for smart content management. For specific feature demands, the NEC MediaPlayer grants easy switching to the integrated Content Management Systems directly.

Benefits

Modern and slim design - robust yet elegant allowing for an unobtrusive integration into any application and environment.

Intuitive Plug & Play solution – even when not familiar with using digital signage, users can facilitate stunning signage creation for immersive real-time visual experiences

Install third party software – expand the NEC MediaPlayer functionality via additional Apps or even switch to your preferred Content Management Systems (CMS) directly from of the NEC MediaPlayer

Everything under control – one single interface is needed to manage both the NEC MediaPlayer and the display directly, via a web-interface or the NEC Display remote control.

Unhindered readability – no reflections from windows or other light sources means no disruption to the visibility of signage content or meeting room presentation

Product Information

Product Name	NEC MultiSync® ME501-MPi4	
Product Group	LCD 50" Midrange Large Format Display (incl. NEC MediaPlayer)	
Order Code	60005373	

Display

Panel Technology	VA with Direct LED backlights	
Screen Size [inch/cm]	50 / 125.7	
Aspect Ratio	16:9	
Brightness [cd/m²]	400	
Contrast Ratio	≥ 8000:1 ¹	
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)	
Colour Depth [bn]	1.073 (8bit + FRC)	
Response Time (typ.) [ms]	8	
Panel Refresh Rate [Hz]	60	
Haze Level [%]	Standard (1)	
Supported Orientation	Landscape; Portrait	

Synchronisation Rate

Horizontal Frequency [kHz]	26 - 135
Vertical Frequency [Hz]	23 - 86

Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	4096 x 2160;	1920 x 1080;	1400 x 1050;	1280 x 720;
	3840 x 2160;	1650 x 1050;	1366 x 768;	1024 x 768
	1920 x 2160;	1600 x 1200;	1360 x 768;	
	1920 x 1200;	1440 x 900;	1280 x 1024;	

Connectivity

Input Video Digital	1 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)	
Input Audio Digital	1 x DisplayPort; 2 x HDMI	
Input Control	LAN 100Mbit; remote control wire (3,5mm jack); RS232	
Input Data	1 x USB 2.0 (MediaPlayer)	
Output Audio Analogue	1 x 3,5 mm jack	
Input Detect	Custom; First; Last	

Open Modular Intelligence

Intel® SDM	accepts Intel® Smart Display Modules Large and Small up to 66 W
Compute Module Slot	RPi Compute Module 4

Sensors

Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption Eco/max. [W]	85 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS

Fn	viron	menta	l Cor	nditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

Mechanical

Dimensions (W x H x D) [mm]	1,128.4 x 649 x 62.6
Weight [kg]	17.3
Bezel Width [mm]	14.9
VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); M6
Ingress Protection	IP5x (front); IP2x (back)
Packaging Dimensions (W x H x D) [mm]	1,298 x 860 x 224
Packaging Weight [kg]	24.1
Colour Bezel	Pantone 426M (black)
Material	Metal

MediaPlayer

Supported File Storage / File System	USB 2.0 / FAT16, FAT32
Internal Storage	32GB eMMC (2GB occupied by OS, 28GB available for files)
Processor	Cortex-A72 (ARMv8) 64-bit SoC @ 1.5GHz
Supported Image Formats	JPG / JPEG; PNG
Supported Video Formats	MP4 / MOV /AVI / MPEG/ WMV / MPG / M4V / VOB / MKV (H.265); MPEG-2; M4K; VP8 / VP9; HTML5
Supported Audio Formats	MP3; AAC; AC-3

Available Options

Accessories	Feet (ST-401/ST-43M); Soundbar (active: SP-ASCM-IQ2 / SP-ASCM-2); Speaker (SP-RM3a);
	Trolley (PDMHM-L); Wall mount (PDW C L and P, PD02W T M L, PD03W T M P)

Green Features

Energy Efficiency	Energy consumption: 85 kWh/1000 h; Energy efficiency class: G; LED backlight
Ecological Standards	EnergyStar 8.0

Additional Features

Safety and Ergonomics Energy Star 8.0 Pixel Failure Class ISO 9241-307, Class 1 Audio Integrated Speakers (10 W + 10 W) Shipping Content 2x AAA batteries; Display; HDMI Cable; Power Cable; Pre-installed MPi4 MediaPlayer Kit; Remote Control; Setup Manual Warranty 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension 2 Operating Hours 18/7 External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP	Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
Audio Integrated Speakers (10 W + 10 W) Shipping Content 2x AAA batteries; Display; HDMI Cable; Power Cable; Pre-installed MPi4 MediaPlayer Kit; Remote Control; Setup Manual Warranty 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension 2 Operating Hours 18/7 External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled	Safety and Ergonomics	Energy Star 8.0
Shipping Content 2x AAA batteries; Display; HDMI Cable; Power Cable; Pre-installed MPi4 MediaPlayer Kit; Remote Control; Setup Manual Warranty 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension ² Operating Hours 18/7 External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled	Pixel Failure Class	ISO 9241-307, Class 1
Remote Control; Setup Manual Warranty 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension ² Operating Hours 18/7 External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled	Audio	Integrated Speakers (10 W + 10 W)
extension ² Operating Hours 18/7 External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled	Shipping Content	
External Control AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PJLink; Scheduled	Warranty	
	Operating Hours	18/7
	External Control	

Remote Management	Automated Email Alerts; NEC NaViSet Administrator 2
Security	Disable HW Buttons; Disable IR Functionality; Disable IR Functionality; Emergency Notification; Emergency Notification
Resistance to Fire	Metal backcover, plastic material certified acc. to UL94-5VB

 $^{^{\}mathrm{1}}$ out of the box conditions, local dimming ON

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 29.04.2021

 $^{^{\}rm 2}$ please refer to terms and conditions of warranty extensions