

ViewSonic® LCD DISPLAY VX3219-PC-MHD

Key Features

- 240Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- 1500R Curved screen for immersive visuals
- Adaptive™ Sync prevents screen tearing
- Full HD resolution for rich detail



Product Description

Upgrade your PC experience with the 32" VX3219-PC-MHD. The large display features a 1500R curve for truly immersive gameplay and the ultra-responsive 240Hz display provides pro-level refresh rates, so you can stay ahead of the competition and enjoy ultra-smooth gaming no matter how intense the action gets. A clean design, with 3-side borderless display and sleek dimensions create a product that delivers all you need. Adaptive™ Sync technology virtually eliminates screen tearing and stuttering for a fluid gaming experience. And the 1ms MPRT response time enables you to react in-game with complete precision, removing ghosting and motion blur. VX3219-PC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for a variety of needs, such as gaming, editing, or watching movies. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

Visit Us — www.viewsonic.com

DISPLAY

| | |
|-------------------------|---|
| Display Size (in.): | 32 |
| Viewable Area (in.): | 31.5 |
| Panel Type: | VA Technology |
| Resolution: | 1920 x 1080 |
| Resolution Type: | FHD |
| Static Contrast Ratio: | 4,000:1 (typ) |
| Dynamic Contrast Ratio: | 80M:1 |
| Light Source: | LED |
| Brightness: | 300 cd/m ² (typ) |
| Colors: | 16.7M |
| Color Space Support: | 8 bit (6 bit + FRC) |
| Aspect Ratio: | 16:9 |
| Response Time (MPRT): | 1ms |
| Viewing Angles: | 178° horizontal, 178° vertical |
| Backlight Life (Hours): | 30000 Hrs (Min) |
| Curvature: | 1500R |
| Refresh Rate (Hz): | 240 |
| Adaptive Sync: | Yes |
| Blue Light Filter: | Yes |
| Flicker-Free: | Yes |
| Color Gamut: | NTSC: 72% size (Typ)sRGB: 103% size (Typ) |
| Pixel Size: | 0.364 mm (H) x 0.364 mm (V) |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) |

COMPATIBILITY

| | |
|------------------------|------------------------------------|
| PC Resolution (max): | 1920x1080 |
| Mac® Resolution (max): | 1920x1080 |
| PC Operating System: | Windows 10 certified; macOS tested |
| Mac® Resolution (min): | 1920x1080 |

CONNECTOR

| | |
|------------------|------------------------|
| 3.5mm Audio Out: | 1 |
| HDMI 2.0: | 2 |
| DisplayPort: | 1 |
| Power in: | External power adapter |

AUDIO

| | |
|--------------------|-----------|
| Internal Speakers: | 2Watts x2 |
|--------------------|-----------|

POWER

| | |
|------------------------|-----------------------|
| Eco Mode (Conserve): | 25W |
| Eco Mode (optimized): | 31W |
| Consumption (typical): | 37W |
| Consumption (max): | 40W |
| Voltage: | AC 100-240V, 50/60 Hz |
| Stand-by: | 0.5W |
| Power Supply: | External |

ADDITIONAL HARDWARE

| | |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

CONTROLS

| | |
|--------------------|---|
| Physical Controls: | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |

OPERATING CONDITIONS

| | |
|----------------------------|-----------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90% |

WALL MOUNT

| | |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

INPUT SIGNAL

| | |
|-----------------------|---|
| Frequency Horizontal: | HDMI (v2.0): 31.469 ~ 291.309KHz, DisplayPort (v1.2): 31.469 ~ 219.309KHz |
| Frequency Vertical: | HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.2): 48 ~ 240Hz |

VIDEO INPUT

| | |
|---------------|--|
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2) |
|---------------|--|

ERGONOMICS

| | |
|----------------------|-----------|
| Tilt (Forward/Back): | -5° / 20° |
|----------------------|-----------|

WEIGHT (IMPERIAL)

| | |
|--------------------------|------|
| Net (lbs): | 10.8 |
| Net Without Stand (lbs): | 9.3 |
| Gross (lbs): | 15.4 |

WEIGHT (METRIC)

| | |
|-------------------------|-----|
| Net (kg): | 4.9 |
| Net Without Stand (kg): | 4.2 |
| Gross (kg): | 7 |

DIMENSIONS (IMPERIAL) (WXHXD)

| | |
|-------------------------------|-------------------|
| Packaging (in.): | 38.2 x 20.6 x 6.7 |
| Physical (in.): | 27.9 x 20.2 x 9 |
| Physical Without Stand (in.): | 27.9 x 16.5 x 3.7 |

DIMENSIONS (METRIC) (WXHXD)

| | |
|------------------------------|-----------------|
| Packaging (mm): | 970 x 523 x 170 |
| Physical (mm): | 709 x 513 x 228 |
| Physical Without Stand (mm): | 709 x 419 x 93 |

GENERAL

| | |
|--------------------|---|
| Regulations: | cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS |
| PACKAGE CONTENTS: | VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 |
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
| Warranty: | *Warranty offered may differ from market to market |
| Country Of Origin: | 28 |