

PTZOptics

A 4th-Generation joystick supporting Network or Serial Camera Control. Experience the full capabilities by pairing it with PTZOptics or HuddleCamHD cameras.

Model Number: PT-JOY-G4

Main Features

- Durable metal housing
- VISCA over IP & Serial control
- PTZOptics Camera On Screen Display control
- Full Pan / Tilt / Zoom camera control
- P/T/Z Speed adjustment on the fly
- Direct exposure & white balance control
- 255 total cameras via network
- 255 camera presets, 9 Quick presets
- Fine tune zoom control dial
- Fine tune focus control knob
- PTZOptics Focus lock & unlock
- Large LCD screen with controller status
- Import / Export settings via network
- 2-Year warranty

What's in the box?

- PT-JOY-G4 Joystick Controller
- 12V 2A DC International Power Supply
- RS-232C cable 8ft (2.4m)
- PT-JOY-G4 Quick Start Guide
- Grounding Pin



Technical Specifications		Operation Specifications	
Connections	RS-232, RS-485, RS-422, RJ-45	Power	6W (12VDC) / PoE (802.3af)
Max Cameras	255 cameras via network 7 cameras via serial VISCA	Working Temp	14° F ~ 122° F (-10° C ~ +50° C)
Recommended Max Distance	RS-232 / RS-422: 50 ft (15m) RS-485: 3,937 ft (1200m) Ethernet: 328 ft (100m)	Working Humidity	10% ~ 90% (non-condensation)
Baud rate	1200 ~ 19200 bps	Weight	4.45 lbs (2.02 kg)
		Dimensions (in.)	11.938 W x 9.25 D x 4.25 H
		Dimensions (mm.)	303.23 W x 234.95 D x 107.95 H