

Product Safety Data Sheet

SDS #: 21-00722

2021-07-14 Revision 2.01

Xerox® B225 Multifunction Printer

Product Description Multi-Function Equipment

3400-4e1

Speed (PPM) 36

Mono / Color Monochrome

ELECTRICAL INPUT INFORMATION

 Voltage (Volts)
 110V-127V
 220V-240V

 Rated Current (Amperes):
 7.0
 3.5

 Frequency (Hertz)
 50/60
 50/60

 Phase Connection
 single
 single

POWER AND HEAT

	Power	Heat Output	Power	Heat Output	
	(Watts)	(BTU/Hr)	(Watts)	(BTU/Hr)	
Active ¹	454	1549	454	1549	
Ready ¹	5.2	17.7	5.1	17.4	
Sleep ¹	1.19	4.06	1.23	4.20	
Standby ¹ (Off/FEMP) ²	0.03	0.10	0.6	0.20	

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%		
Ambient Temperature	50-90 °F	/	10-32 °C

PRODUCT SIZE

Depth 16.5	in.	42.0	cm
Width 14.7	in.	37.3	cm
Height 13.5	in.	34.3	cm
Weight 25.6	bs	11.6	kg

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE: Class 1 Laser Product

Chemical Emission Test Methodology RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

 PARAMETER
 Emission Rate

 Total Volatile Organic Compounds (TVOC)
 5.6 mg/h

 Dust
 0.84 mg/h

 Ozone
 <0.23 mg/h</td>

 Styrene
 0.06 mg/h

 Benzene
 0.02 mg/h

² FEMP - Federal Energy Management Program



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

Sound Power Level LwAd (dBA) Sound Pressure Level LpAd (dBA)

Run - continuous

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177 Inquiries US only: 1-800-828-6571 Contact US only: usa.xerox.EHS@xerox.com Contact Non US only: ehs-europe@xerox.com