

DIGITUS Displayport connection cable, DP, w/ amp.

AK-340105-150-S
EAN 4016032433712



Displayport connection cable, DP, w/ amp. M/M, 15.0m, w/lock, UHD 4K, DP 1.2, bl, gold

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

A/V connection over long distances without signal loss

- Supported Video format: 4K/2K@24Hz, 4K/2K@30Hz or 4K/2K@60Hz
- Supported Video Resolution: 4K (3840x2160) @ 60 Hz, Full HD (1920x1080) @ 120 Hz
- No external power supply needed
- Save and reliable connection based on the snap fastener at connector
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)

- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: plastic
- Interlock: Snap fastener
- Wire material: CU
- Length: 15 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	7	10.30	38.10	31.10	30.20	35,784.30
Packaging Unit Inside	1	1.47	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.47	33.50	33.50	6.50	7,294.62
Net single without Packaging	1	1.36	22.00	22.00	6.50	0.00

More images:

