


# ExCam XF P1377 Explosion-Protected Camera

## Zone-certified fixed camera with excellent image quality

Certified (ATEX, IECEx, EAC Ex, IA and PESO) for use in potentially combustible environments, this lightweight camera offers high quality, high resolution images of people and objects. Featuring Axis Lightfinder and Axis Forensic WDR, it delivers true colors and great details in challenging light or near darkness. It includes electronic image stabilization for stable images despite vibration. And, intelligent i-CS lens technology facilitates fast and easy installation with remote zoom. Built-in cybersecurity features such as signed firmware and secure boot ensure the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with support for H.264/H.265 significantly lowers bandwidth and storage requirements.

- > 30 fps in 5 MP or up to 180 fps in HDTV 720p
- > Lightfinder and Forensic WDR
- > Zipstream supporting H.264 and H.265
- > Signed firmware and secure boot
- > ATEX, IECEx, EAC Ex, IA and PESO



# ExCam XF P1377 Explosion-Protected Camera

<b>Camera</b>		<b>Event conditions</b>	Analytics, shock detection, edge storage events, supervised external input, audio level, time scheduled, MQTT subscribe
<b>Image sensor</b>	1/2.7" progressive scan RGB CMOS	<b>Event actions</b>	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, WDR mode, day/night mode MQTT publish
<b>Lens</b>	IR-corrected i-CS lens Varifocal 3.9–10 mm, F1.5 4:3 aspect ratio: Horizontal field of view: 75°–31° Vertical field of view: 55°–23° 16:9 aspect ratio: Horizontal field of view: 75°–31° Vertical field of view: 41°–17° Remote zoom, remote focus	<b>Data streaming</b>	Event data
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Built-in installation aids</b>	Focus assistant, pixel counter, remote back focus, autorotation
<b>Minimum illumination</b>	5 MP 25/30 fps with Forensic WDR and Lightfinder: Color: 0.15 lux, at 50 IRE F1.5 B/W: 0.03 lux, at 50 IRE F1.5	<b>Analytics</b>	
<b>Shutter speed</b>	WDR: 1/33500 s to 1/5 s No WDR: 1/5000 s to 1/5 s	<b>Applications</b>	<b>Included</b> AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard <b>Supported</b> AXIS Live Privacy Shield, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>System on chip (SoC)</b>		<b>Cybersecurity</b>	
<b>Model</b>	ARTPEC-7	<b>Edge security</b>	<b>Software:</b> Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption <b>Hardware:</b> Secure boot
<b>Memory</b>	1 GB RAM, 512 MB Flash	<b>Network security</b>	IEEE 802.1X (EAP-TLS) <sup>a</sup> , HTTPS/HSTS <sup>a</sup> , TLS v1.2/v1.3 <sup>a</sup> , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
<b>Video</b>		<b>Documentation</b>	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="http://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="http://axis.com/cybersecurity">axis.com/cybersecurity</a>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG	<b>General</b>	
<b>Resolution</b>	2592x1944 (5 MP) to 160x90 2688x1512 (4 MP) to 160x90 1280x720 (HDTV 720p) to 160x90	<b>Casing</b>	IP68-rated, EN 1.4404 (ASTM 316L) stainless steel casing for maximum corrosion protection Casing manufactured and certified by Samcon Prozessleittechnik GmbH, <a href="http://www.samcon.eu">www.samcon.eu</a>
<b>Frame rate</b>	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 4 MP: 25/30 fps (50/60 Hz) Capture mode HDTV 720p: 180 fps	<b>Power</b>	<b>Camera:</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 10.7 W, typical 5.4 W <b>Heater:</b> 24 V DC, max 40 W 24 V DC is required for operating at temperatures below 0 °C (32 °F).
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	<b>Connectors</b>	5 m (16 ft) pigtail cable for network (Cat 6, RJ45 connector) and power
<b>Multi-view streaming</b>	Up to 8 individually cropped out view areas	<b>Storage</b>	Pre-installed AXIS Surveillance microSDXC Card 128 GB Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview	<b>Operating conditions</b>	-60 °C to 60°C (-76 °F to 140 °F) Humidity 10–100% RH (condensing)
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Network</b>		<b>Approvals</b>	EMC EN 55035, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2 <b>Environment</b> IEC/EN 60529 IP68 <b>Network</b> NIST SP500-267 <b>Explosion</b> EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-31, TR CU 012/2011, GOST R IEC 60079-0, GOST IEC 60079-1, GOST R IEC 60079-31
<b>Security</b>	IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, user access log, centralized certificate management	<b>System integration</b>	
<b>Network protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at <a href="http://axis.com">axis.com</a> One-Click Cloud Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T, specification at <a href="http://onvif.org">onvif.org</a>
<b>System integration</b>		<b>Onscreen controls</b>	Electronic image stabilization Day/night shift Defogging Wide dynamic range

<b>Certifications</b>	<p>Model key: T08-VA2.3.K3.BOR2-LL.H-005.N-P  ATEX: II 2 G Ex db IIC T5 Gb, II 2 D Ex tb IIIC T95°C Db  Certificate: TÜV 18 ATEX 8218X  IECEX: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db  Certificate: IECEX TUR 18.0023X  IA: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db  Certificate: MASC MS/18-3256X  EAC Ex: 1Ex db IIC T5 Gb, Ex tb IIIC T 95°C Db  Series: T8, Model: T08-VA2.3.  Certificate: RU C-DE.HA65.B.01652/22  PESO: Ex db IIC T5 Gb  Certificate: A/P/HQ/KA/104/5735  UKCA: II 2 G Ex db IIC T5 Gb, II 2 D Ex tb IIIC T95 °C Db  Certificate: TÜV 22 UKEX 7137 X</p>	For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Dimensions</b>	<p>ø 113 mm (4.4 in)  Height: 160.5 mm (6.3 in )  Length: 334 mm (13.1 in )</p>	
<b>Weight</b>	7.8 kg (17.2 lb)	
<b>Included accessories</b>	<p>Installation Guide, Windows® decoder 1-user license, SKDP03-T  Cable ExCam 5 meter, AXIS Surveillance microSDXC Card 128 GB</p>	
<b>Optional accessories</b>	<p>Wall Mount ExCam XF, Pole Mount ExCam XF,  EXTB-3 Junction Box ExCam,  Non-armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft),  Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft),  Ex Connection Rail 4-port PoE PS 24,  Ex Connection Rail 8-port PoE PS 24, Weathershield ExCam XF</p>	
<b>Video management software</b>		AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Languages</b>		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Polish
<b>Warranty</b>		5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Sustainability</b>		
<b>Substance control</b>		<p>PVC free  Free of hazardous brominated and chlorinated flame retardants (BFR/CFR free)  RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018  REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see <a href="http://echa.europa.eu">echa.europa.eu</a></p>
<b>Environmental responsibility</b>		<p><a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>  Axis Communications is a signatory of the UN Global Compact, read more at <a href="http://unglobalcompact.org">unglobalcompact.org</a></p>
		<p>a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<a href="http://www.openssl.org/">http://www.openssl.org/</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</i></p>