# Eaton 3S550B

# Catalog Number: 3S550B

Eaton 3S 550 BS, 550 VA, 330W, Input : UK, Outputs :(3) UK, (3) UK surge only, USB Communication, Tower

# General specifications



**Product Name** 

Eaton 3S Gen2 UPS

EAN

3553340705052

**Product Height** 

140 mm

**Product Weight** 

3.2 kg

Certifications

IEC/EN 62040-1

EAC

IEC/EN 62040-2

CE

Catalog Number

3S550B

Product Length/Depth

86 mm

**Product Width** 

325 mm

Compliances

CE Marked

Photo is representative



#### **Battery**

Battery type

Sealed, lead-acid

Runtime graph

View runtime graph

Battery replacement

User replaceable

Battery quantity

1

Battery management

Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable

Battery rating

12 V / 5 Ah

Extended battery capability

No

#### Electrical output

Receptacle

(3) BS, (3) BS surge only

Voltage

230V

Wattage

330W

Output power factor

0.6

Output voltage range

184-264 V (adjustable to 161-284 V)

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

0

Feed type

1

Topology

Offline/Standby

VA rating

550 VA

# Electrical input

Input connection

Protective contact (SCHUKO)

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50-60 Hz

Input cord length

1.5 m

Input voltage range

184-264 V (adjustable to 161-284 V)

Input frequency range

46-70 Hz

#### Communications

Includes network card

No

Communication

USB port (HID compliant)

Ethernet interface

No

User interface

LEDs

Potential free switch contact

No

**Expansion slots** 

No

#### Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

#### Type of interface

USB

# **Environmental**

Altitude

2000 m

Noise level

<25 dB at 1 meter

Relative humidity

0-85% non-condensing

# Additional specifications

#### Construction type

Free standing model

#### Package contents

USB cable

Quickstart guide

Safety instructions

#### Phase (output)

1

#### Auto shutdown function

Yes

#### Color

Black/White

#### Efficiency

98

# Rack mounting kit

No

#### Phase (input)

1

#### Surge protection

Yes

# Resources



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

