

Delock USB Type-C™ 3.2 Gen 2 to SATA Converter

Description

This converter by Delock can be connected via USB Type-A interface to a PC or laptop. Thus a **2.5" or 3.5" SATA HDD or SSD** with a 22 pin SATA interface can be used.



Item no. 64188

EAN: 4043619641888

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - 1 x SATA 6 Gb/s 22 pin receptacle
 - 1 x DC jack
- Chipset: Asmedia ASM235CM
- For 2.5" and 3.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 6 Gb/s
- LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 72 x 29 x 14 mm

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.5 mm

outside: ø ca. 5.5 mm

length: ca. 10 mm

System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.2.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- Surface Pro 7
- PC or laptop with a free USB Type-A port

Package content

- Converter
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Power supply
- User manual

Images



General

Suitable for data medium:	2.5" 3.5"
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Android 10.0 or above Mac OS 11.2.3 or above Windows 11 Linux Kernel 5.11 or above

Interface

Connector 1:	1 x USB 10 Gbps USB Type-C™ female
Connector 2:	1 x SATA 6 Gb/s 22 pin receptacle
connector 3:	1 x DC jack

Technical characteristics

Chipset:	Asmedia ASM235CM
Data transfer rate:	6 Gb/s

Physical characteristics

Cable length:	1 m
---------------	-----