

MPN: LVO231805UNI


Fiber patch cords LC Uniboot to LC Uniboot duplex OM3 5m 3.0mm LSZH (Grade C)

This Uniboot cable comes with a lot of great features to take your networking setup to the next level, Uniboot cables comes with both the fibre leads coated in a single jacket, meaning there is more room for airflow in the rack. This also means the insertion loss is low.

Another special feature of the Uniboot cable is the option to switch polarities, simply remove the top cover and you can swap the connectors to change the polarity, no need to swap to another cable with Uniboot.

This cable lives up to the OM3 fibre standard to connect to high speed and legacy networks like 10/40/100 gigabit. This cable standard is ideal for for connecting 40G BIDI SR, 10G SR, QSFP+, SFP+ transceivers etc.

The cable is made of LSZH material to live up to Telecordia, EIA TIA or IEC standards.



- UniBoot to minimize insertionloss
- Easy to handle
- LSZH (Low Smoke Zero Halogen) and flame retardant
- Pre tested with test report
- Reverse Polarity—with a few simple steps, the connectors polarity of the LC Uniboot Fibre patch cables can be reversed without need of connector re-termination.
- Quick Release Latch—the latch of LC Uniboot Fibre patch cable allows for the quick and easy release of this connector from the adapter panel, which makes great sense in the growing trend of high density applications.
- Fibre Standard G.652.D

Specifications

Features		
Cable length	5 m	
Cable type	Duplex	
Certification	Rohs	
Cladding diameter	150 µm	
Connector 1	LC/UPC	
Connector 1 gender	Male	
Connector 2	LC/UPC	
Connector 2 gender	Male	
Connector gender	Male/Male	
Ethernet interface type	10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet, Fast Ethernet	
Fiber mode structure	Multi-mode	
Fibre optic type	OM3	
Full duplex	Yes	

Features	Halogen-free	Yes
	Insertion loss	0.14 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Blue
	REACH compliance	Yes
	Return loss	38.42 dB
	RoHS compliance	Yes
	Wavelengths supported	850, 1300 nm
Packaging data	Quantity per pack	1 pc(s)
Technical details	Sustainability certificates	REACH, RoHS
	Sustainability compliance	Yes
Vendor information	Brand Name	Lanview
	Warranty	5 Year(s)

Other products in this series

Cable length	
1	LVO231801UNI
2	LVO231802UNI
3	LVO231803UNI
5	LVO231805UNI

Other images

