

# DELTA <sup>RGB</sup> DDR5

Gaming Desktop Memory



**DELTA RGB DDR5**

## DELTA RGB DDR5

With a refreshing visual experience modeled after a stealth aircraft, the T-FORCE DELTA RGB DDR5 offers a 120°Ultra-Wide Lighting angle that supports lighting software from various manufacturers. In addition to support the latest Intel XMP3.0 one-click OC technology, the DELTA RGB DDR5 is also equipped with PMIC and on-die ECC to ensure stable, efficient power distribution across all components for system stability and performance.

### Main Feature

- RGB Colors & 120°Ultra-Wide Lighting
- Supports Intel XMP3.0 for One-Click Overclocking
- Power Management IC (PMIC) Equipped for Stable, Efficient Power Usage
- Strengthened PMIC Cooling Design
- On-die ECC for Stable System
- High-Quality ICs Selected for Stability & Reliability
- Equipped with Smart RGB IC Controller that Supports Various Lighting Effect Software



### Specification

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM								
Frequency	6400	6200	6000	6000	5600	5600	5600	5600	5200
Capacity	16GBx2	16GBx2	16GBx2	16GBx2	16GBx2	16GBx2	16GBx2	16GBx2	16GBx2
Latency	40-40-40-84	38-38-38-78	30-36-36-76	38-38-38-78	32-36-36-76	36-36-36-76	36-36-36-76	40-40-40-84	40-40-40-76
Data Transfer Bandwidth	51,200 MB/s (PC5 51200)	49,600 MB/s (PC5 49600)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	44,800 MB/s (PC5 44800)	44,800 MB/s (PC5 44800)	44,800 MB/s (PC5 44800)	44,800 MB/s (PC5 44800)	41,600 MB/s (PC5 41600)
Voltage	1.35 V	1.25 V	1.35 V	1.25 V	1.2 V	1.2 V	1.2 V	1.2 V	1.25 V
Compatibility	Intel: Z690/B660								
Dimensions	46.1(H) x 144.2(L) x 7(W)mm								
Warranty	Lifetime warranty								

## Ordering Information

Color	Frequency	CAS Latency/Voltage	Capac	Team P/N
Black	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GBx2	FF3D532G5200HC40CDC01
	DDR5-5600 (PC5-44800)	CL32-36-36-76 1.2V	16GBx2	FF3D532G5600HC32DC01
		CL36-36-36-76 1.2V	16GBx2	FF3D532G5600HC36BDC01
		CL40-40-40-84 1.2V	16GBx2	FF3D532G5600HC40BDC01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GBx2	FF3D532G6000HC30DC01
		CL38-38-38-78 1.25V	16GBx2	FF3D532G6000HC38ADC01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GBx2	FF3D532G6200HC38ADC01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GBx2	FF3D532G6400HC40BDC01

## Ordering Information

Color	Frequency	CAS Latency/Voltage	Capac	Team P/N
White	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GBx2	FF4D532G5200HC40CDC01
	DDR5-5600 (PC5-44800)	CL32-36-36-76 1.2V	16GBx2	FF4D532G5600HC32DC01
		CL36-36-36-76 1.2V	16GBx2	FF4D532G5600HC36BDC01
		CL40-40-40-84 1.2V	16GBx2	FF4D532G5600HC40BDC01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GBx2	FF4D532G6000HC30DC01
		CL38-38-38-78 1.25V	16GBx2	FF4D532G6000HC38ADC01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GBx2	FF4D532G6200HC38ADC01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GBx2	FF4D532G6400HC40BDC01

※The frequency and stability of the overclocking memory when automatic reading of the overclocking value (XMP or D.O.C.P) is turned on will vary depending on the difference between the motherboard and CPU. Check "Product Compatibility Inquiry" before purchase for further info <https://www.teamgroupinc.com/en/support/compatibility.php>

※We reserve the right to modify product specifications without prior notice.