

Display		Driftsbetingelser	
Overfladehårdhed	3H	Driftstemperatur (T-T)	0 - 40 °C
Farvedybde	6 Bit	Opbevaringstemperatur (T-T)	-25 - 55 °C
sRGB-dækning (typisk)	99%	Relativ luftfugtighed ved drift (H-H)	10 - 85%
Adobe RGB dækning	77%	Relativ luftfugtighed ved opbevaring (H-H)	5 - 93%
3D	✗	Driftshøjde	0 - 5000 m
Præstation		Ikke-drift højde	5000 - 12192 m
NVIDIA G-SYNC *	✗	Vægt & størrelser	
Hurtig opladning	✓	Bredde (med stativ)	535,2 mm
Flimmerfri teknologi	✓	Dybde (med stativ)	203 mm
Lav Blue Light teknologi	✓	Højde (med stativ)	533,5 mm
Multimedie		Vægt (med stativ)	5,5 kg
Antal højttalere	2	Bredde (uden stativ)	533,5 mm
Udgangseffekt (RMS)	4 W	Dybde (uden stativ)	46,5 mm
Indbyggede højttaler(e) *	✓	Højde (uden stativ)	354,4 mm
Indbygget mikrofon	✗	Vægt (uden stativ)	3,71 kg
Indbygget kamera *	✗	Emballeringsdata	
Design		Pakkebredde	752 mm
Markedspositionering *	Forretning	Pakkedybde	168 mm
Produktfarve *	Sort	Pakkehøjde	422 mm
Frontkantfarve	Sort	Pakkevægt	7,5 kg
Aftageligt stativ	✓	Pakketype	Kasse
Farve	Sort	USB-kabellængde	1,8 m
Porte & Grænseflader		Emballage indhold	
Indbygget USB-hub *	✓	Stativ inkluderet	✓
USB-hub-version	3.2 Gen 1 (3.1 Gen 1)	Kabler inkluderet	Vekselstrøm, HDMI, DisplayPort
Antal USB type-A downstream-porte	4	Lyd kabellængde	1,8 m
Antal VGA-porte (D-sub)	1	DisplayPort kabellængde	1,8 m
DVI-port	✓	HDMI-kabellængde	1,8 m
Antal DVI-D-porte	1	Strømkabellængde	1,8 m
HDMI *	✓	Bæredygtighed	
Antal HDMI-porte	1	Bæredygtighedscertifikater	EPEAT Silver, TCO
HDMI-version	1.4	Indeholder ikke	Kviksølv, PVC/BFR
Antal DisplayPorts	1	Andre funktioner	
DisplayPort-version	1.2	Kapabilitet	VESA-P1
Lydingang	✓	Tænd-/slukkontakt	✓
Udgang til hovedtelefoner *	✓	TV-tuner, integreret	✗
Udgange til hovedtelefoner	1	Udvendigt finish type	Tekstureret
Tilslutning af hovedtelefoner	3,5 mm	Ingen tungmetaller	Hg (kviksølv)
Mikrofonindgang	✓	Bezel tykkelse type	Rammeløs
Ergonomisk		Garantiperiode	3 År
VESA montering *	✓	Compliance-certifikater	WEEE, REACH
Panel montering grænseflade	100 x 100 mm	Gennemsnitstid mellem fejl (MTBF)	50000 t
Slot til kabellås *	✓	Lyseffekter	✗
Kabellåseslids type	Kensington	Certificering	WEEE, REACH compliant, RoHS compliant, CB, TUV-GS-Mark, EAC, FCC, Microsoft WHQL
Højdejustering *	✓	Genbrug af data	
		Genanvendelige emballeringsmaterialer	100%
		Genbrugsplast	85%
		Logistik data	
		Harmoniseret systemkode (HS)	85285210



4038986146241

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.